					DEPARTMEN [*]	TATE OF UTAH T OF NATURAL RES DF OIL, GAS AND M		S		AMENDE	FOR D REPORT		
			APPLICA	ATION FOR	PERMIT TO DRILL				1. WELL NAME and NU	JMBER .C Tribal 4-	-36D-47		
2. TYPE (OF WORK	DRILL NEW WE	ELL ((iii)	REENTER P	&A WELL DEEPEN	I WELL			3. FIELD OR WILDCAT UNDESIGNATED				
4. TYPE OF WELL 5.							5. UNIT or COMMUNI	FIZATION A	GREEME	NT NAM	E		
6. NAME	OF OPERATO	R	Oli Well		ETT CORP				7. OPERATOR PHONE	303 312-	8134		
8. ADDRE	SS OF OPERA		1099 18th 9						9. OPERATOR E-MAIL			ım	
		IMBER		0.1001 0.10 2.	11. MINERAL OWNERS				12. SURFACE OWNER	SHIP			
		2OG0005500	12 = 'fee')		FEDERAL INI	DIAN 📵 STATE (J FEI	E()	FEDERAL INI	DIAN (III) R PHONE (i	STATE (E ()
									16. SURFACE OWNE			·	
					18. INTEND TO COMM	MINGLE PRODUCTION	N FROM		19. SLANT				
	2 = 'INDIAN')				MULTIPLE FORMATIO				VERTICAL DIF	RECTIONAL	а но	RIZONT	AL 🗀
20. LOC	ATION OF WE	LL		F	OOTAGES	QTR-QTR		CTION	TOWNSHIP	RAN			RIDIAN
LOCATI	TYPE OF WORK DRILL NEW WELL OII Well CANAME OF OPERATOR BILL BA ADDRESS OF OPERATOR MINERAL LEASE NUMBER EDERAL, INDIAN, OR STATE) 20G0005500 NAME OF SURFACE OWNER (if box 12 = 'fee') ADDRESS OF SURFACE OWNER (if box 12 = 'fee') INDIAN ALLOTTEE OR TRIBE NAME box 12 = 'INDIAN') Uintah and Ouray DIATION OF WELL COCATION OF WELL DOCATION AT SURFACE DE OP OF Uppermost Producing Zone A Total Depth COUNTY DUCHESNE ELEVATION - GROUND LEVEL 6686 Fring Hole Size Casing Size Length Well Cond 26 16 0 - 80 6 Surf 12.25 9.625 0 - 800 3 Prod 8.75 9.625 0 - 6246 1 VERIFY THE FOLLOWING ARE AT VERIFY THE FOLLOWING ARE AT VERIFY THE FOLLOWING ARE AT DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OF STATUS OF SURFACE OWNER AGREE) AME Venessa Langmacher			669 F	NL 699 FWL	NWNW		36	4.0 S	7.0	W		U
Top of U	Jppermost Pro	oducing Zone		810 F	NL 810 FWL	NWNW		36	4.0 S	7.0	W		U
At Tota	Depth			810 F	NL 810 FWL	NWNW		36	4.0 S	7.0	W	U	
21. COUI	NTY	DUCHESNE			22. DISTANCE TO NEA	AREST LEASE LINE (F	Feet)		23. NUMBER OF ACRI	ES IN DRILI 640	ING UNIT		
					25. DISTANCE TO NEA (Applied For Drilling		E POOL		26. PROPOSED DEPTI		VD: 6240		
27. ELEV	ATION - GROU				28. BOND NUMBER	LPM8874725			29. SOURCE OF DRIL WATER RIGHTS APPR		BER IF AP	PLICABL	E
					Hole, Casing	, and Cement Info	ormatio	n					
String	Hole Size	Casing Size	Lengt	h Weig	nt Grade & Thread	Max Mud Wt.			Cement		Sacks	Yield	Weight
Cond	26	16	0 - 8	0 65.0	Unknown	8.8			No Used		0	0.0	0.0
Surf	12.25	9.625	0 - 80	36.0	J-55 ST&C	8.8		Halliburto	n Light , Type Unkr	own	70	3.16	11.0
							На	alliburton f	Premium , Type Un	known	210	1.36	14.8
Prod	8.75	9.625	0 - 624	46 17.0	P-110 LT&C	9.6	-	Unknown 580 2.31				11.0	
		<u> </u>	<u> </u>						Unknown		660	1.42	13.5
					Α	ATTACHMENTS							
	VE	RIFY THE FOL	LOWING	ARE ATTA	CHED IN ACCORDAN	NCE WITH THE UTA	AH OIL	AND GAS	CONSERVATION G	ENERAL	RULES		
► ∨	/ELL PLAT OR	MAP PREPARED I	BY LICENS	SED SURVEY	OR OR ENGINEER	✓ cow	IPLETE D	ORILLING PL	AN				
Al	FIDAVIT OF S	TATUS OF SURFA	CE OWNE	R AGREEME	NT (IF FEE SURFACE)	FOR	M 5. IF OF	PERATOR IS	OTHER THAN THE LE	EASE OWN	ER		
DI DI	RECTIONAL S	URVEY PLAN (IF	DIRECTIO	NALLY OR F	ORIZONTALLY DRILLED	о) горо	OGRAPHI	ICAL MAP					
NAME V	enessa Langm	acher		ТІ	TLE Senior Permit Analys	st	PI	HONE 303	312-8172				
SIGNATURE DATE 05/22/2013 EMAIL vlangmacher@billbarrettcorp.com													
				AF	PROVAL			Boll	Rejill				
<u></u>	Per								Manager				

BILL BARRETT CORPORATION <u>DRILLING PLAN</u>

LC Tribal 4-36D-47

NW NW, 669' FNL and 699' FWL, Section 36, T4S-R7W, USB&M (surface hole) NW NW, 810' FNL and 810' FWL, Section 36, T4S-R7W, USB&M (bottom hole) Duchesne County, Utah

1 - 2. <u>Estimated Tops of Geological Markers and Formations Expected to Contain Water, Oil and Gas and Other Minerals</u>

<u>Formation</u>	Depth – MD	Depth - TVD
Green River	925'	925'
Mahogany	1,576'	1,575'
Lower Green River*	2,738'	2,735'
Douglas Creek	3,520'	3,515'
Black Shale	4,320'	4,315'
Castle Peak	4,555'	4,550'
Uteland Butte	4,880°	4,875'
Wasatch*	5,085'	5,080'
TD	6,246'	6,240'

*PROSPECTIVE PAY

The Wasatch and the Lower Green River are primary objectives for oil/gas.

Base of Useable Water = 5,501'

3. BOP and Pressure Containment Data

Depth Intervals	BOP Equipment							
0 – 800' No pressure control required								
800' – TD	11" 5000# Ram Type BOP							
	11" 5000# Annular BOP							
- Drilling spool to a	accommodate choke and kill lines;							
- Ancillary equipme	ent and choke manifold rated at 5,000 psi. All BOP and BOPE tests will be in							
accordance with the	he requirements of onshore Order No. 2;							
- The BLM and the	State of Utah Division of Oil, Gas and Mining will be notified 24 hours in							
advance of all BC	advance of all BOP pressure tests.							
- BOP hand wheels	may be underneath the sub-structure of the rig if the drilling rig used is set up							
To operate most e	fficiently in this manner.							

4. <u>Casing Program</u>

Hole Size	SETTING DEPTH		SETTING DEPTH Casing Casing				
	(FROM)	(<u>TO</u>) <u>Size</u>		Weight	Grade	Thread	Condition
26"	Surface	80'	16"	65#			
12 1/4"	Surface	800'	9 5/8"	36#	J or K 55	ST&C	New
8 3/4"	Surface	TD	5 ½"	17#	P-110	LT&C	New

RECEIVED: May 22, 2013

Bill Barrett Corporation Drilling Program LC Tribal 4-36D-47 Duchesne County, Utah

5. <u>Cementing Program</u>

16" Conductor Casing	Grout
9 5/8" Surface Casing	Lead: 70 sx Halliburton Light Premium with additives
	mixed at 11.0 ppg (yield = $3.16 \text{ ft}^3/\text{sx}$) circulated to surface
	with 75% excess. TOC @ Surface
	Tail: 210 sx Halliburton Premium Plus cement with
	additives mixed at 14.8 ppg (yield = $1.36 \text{ ft}^3/\text{sx}$), calculated
	hole volume with 75% excess. TOC @ 300'
5 ½" Production Casing	Lead: 580 sx Tuned Light cement with additives mixed at
	11.0 ppg (yield = $2.31 \text{ ft}^3/\text{sx}$). TOC @ 300'
	Tail: 660 sx Halliburton Econocem cement with additives
	mixed at 13.5 ppg (yield = $1.42 \text{ ft}^3/\text{sx}$). Top of cement to
	be determined by log and sample evaluation; estimated TOC
	@ 3,820'

6. <u>Mud Program</u>

Interval	Weight	<u>Viscosity</u>	Fluid Loss (API filtrate)	<u>Remarks</u>
0'-80'	8.3 - 8.8	26 - 36	NC	Freshwater Spud Mud Fluid
				System
80' - 800'	8.3 - 8.8	26 - 36	NC	Freshwater Spud Mud Fluid
				System
800' – TD	8.6 - 9.6	42-52	20 cc or less	DAP Polymer Fluid System

Note: Sufficient mud materials to maintain mud properties, control lost circulation and to contain "kicks" will be available at wellsite. BBC may require minor amounts of diesel to be added to its fluid system in order to reduce torque and drag.

7. Testing, Logging and Core Programs

Cores	None anticipated;
Testing	None anticipated; drill stem tests may be run on shows of interest;
Sampling	30' to 50' samples; surface casing to TD. Preserve samples all show intervals;
Surveys	MWD as needed to land wellbore;
Logging	DIL-GR-SP, FDC-CNL-GR-CALIPER-Pe-Microlog, Sonic-GR (all TD to surface).
	FMI & Sonic Scanner to be run at geologist's discretion.

8. Anticipated Abnormal Pressures or Temperatures

No abnormal pressures or temperatures or other hazards are anticipated.

Maximum anticipated bottom hole pressure equals approximately 3115 psi* and maximum anticipated surface pressure equals approximately 1742 psi** (bottom hole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

^{*}Max Mud Wt x 0.052 x TD = A (bottom hole pressure)

^{**}Maximum surface pressure = A - (0.22 x TD)

Bill Barrett Corporation Drilling Program LC Tribal 4-36D-47 Duchesne County, Utah

9. Auxiliary Equipment

- a) Upper kelly cock; lower Kelly cock will be installed while drilling
- b) Inside BOP or stab-in valve (available on rig floor)
- c) Safety valve(s) and subs to fit all string connections in use Mud monitoring will be visually observed

10. Location and Type of Water Supply

Water for the drilling and completion will be trucked from the Duchesne City Culinary Water Dock located in Sec. 1, T4S, R5W water right number 43-180.

11. <u>Drilling Schedule</u>

Location Construction: January 2014 Spud: January 2014 Duration: 15 days drilling time

6 days completion time

Well Name:

% Excess:

Top of Tail:

75%


300



LAKE CANYON & BLACK TAIL RIDGE CEMENT VOLUMES

LC Tribal 4-36D-47

Surface Hole Data: Calculated Data: Total Depth: 800 Lead Volume: 164.4 Top of Cement Lead Fill: 300' OD of Hole: 12.250" Tail Volume: 274.0 500' OD of Casing: 9.625 Tail Fill: Cement Data: Calculated # of Sacks: ft°/sk Lead Yield: 3.16 # SK's Lead: % Excess 75% Top of Lead: 0' Tail Yield: 1.36 ft°/sk # SK's Tail:





LC Tribal 4-36D-47 Proposed Cementing Program


Job Recommendation		Su	face Casing
Lead Cement - (300' - 0')			
Halliburton Light Premium	Fluid Weight:	11.0	lbm/gal
5.0 lbm/sk Silicalite Compacted	Slurry Yield:	3.16	ft ³ /sk
0.25 lbm/sk Kwik Seal	Total Mixing Fluid:	19.48	Gal/sk
0.125 lbm/sk Poly-E-Flake	Top of Fluid:	0'	
2.0% Bentonite	Calculated Fill:	300'	
	Volume:	29.28	bbl
	Proposed Sacks:	70	sks
Tail Cement - (TD - 300')			
Premium Cement	Fluid Weight:	14.8	lbm/gal
2.0% Calcium Chloride	Slurry Yield:	1.36	ft ³ /sk
	Total Mixing Fluid:	6.37	Gal/sk
	Top of Fluid:	300'	
	Calculated Fill:	500'	
	Volume:	48.80	bbl
	Proposed Sacks:	210	sks


Job Recommendation		Produc	tion Casing
Lead Cement - (3820' - 300')			
Tuned Light [™] System	Fluid Weight:	11.0	lbm/gal
	Slurry Yield:	2.31	ft ³ /sk
	Total Mixing Fluid:	10.65	Gal/sk
	Top of Fluid:	300'	
	Calculated Fill:	3,520'	
	Volume:		
	Proposed Sacks:	580	sks
Tail Cement - (6246' - 3820')			
Econocem [™] System	Fluid Weight:	13.5	lbm/gal
0.125 lbm/sk Poly-E-Flake	Slurry Yield:	1.42	ft ³ /sk
1.0 lbm/sk Granulite TR 1/4	Total Mixing Fluid:		Gal/sk
	Top of Fluid:	3,820'	
	Calculated Fill:	2,426'	
	Volume:		bbl
	Proposed Sacks:	660	sks


RECEIVED: May 22, 2013











BILL BARRETT CORP

DUCHESNE COUNTY, UT (NAD 27) 4-36D-47 LC Tribal 4-36D-47 LC Tribal

Wellbore #1

Plan: Design #1

Standard Planning Report

17 May, 2013



COMPANY DETAILS: BILL BARRETT CORP

Calculation Method: Minimum Curvature

Error System: ISCWSA

Scan Method: Closest Approach 3D Error Surface: Elliptical Conic Warning Method: Error Ratio SITE DETAILS: 4-36D-47 LC Tribal Lake Canyon

Site Latitude: 40° 5' 42.349 N Site Longitude: 110° 37' 49.001 W

Positional Uncertainity: 0.0 Convergence: 0.56 Local North: True

WELL DETAILS: 4-36D-47 LC Tribal

Ground Level: 6685.0

+N/-S +E/-W Northing Easting Latittude Longitude Slot 0.0 0.0 642867.11 2243306.04 40° 5′ 42.349 N 110° 37′ 49.001 W

	WELLBORE TARGET DETAILS (LAT/LONG)										
4-3	Name	TVD	+N/-S	+E/-W	Latitude	Longitude	Shape				
	36D-47 LC Tribal 3PT MKR	3890.0	-140.6	111.1	40° 5' 40.960 N	110° 37' 47.572 W	Rectangle (Sides: L200.0 W200.0)				
	4-36D-47 LC Tribal PBHL	6240.0	-140.6	111.1	40° 5' 40.960 N	110° 37' 47.572 W	Rectangle (Sides: L200.0 W200.0)				


-37


					SE	CTION	DETAIL	S				ŀ
S	ec MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target		
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	-		ı
2	900.0	0.00	0.00	900.0	0.0	0.0	0.00	0.00	0.0			l
3	1149.4	3.74	141.69	1149.2	-6.4	5.0	1.50	141.69	8.1			l
4	3646.3	3.74	141.69	3640.8	-134.2	106.0	0.00	0.00	171.0			l
5	3895.7	0.00	0.00	3890.0	-140.6	111.1	1.50	180.00	179.2	4-36D-47 LC Trib	al 3PT MKF	Ħ
6	6245.7	0.00	0.00	6240.0	-140.6	111.1	0.00	0.00	179.2	4-36D-47 LC Trib	al PBHL	l

FORMATION TOP DETAILS TVDPath **MDPath** Formation 925.0 925.0 Green River 1575.0 1576.1 Mahogany 2735.0 3515.0 2738.6 TGR3 3520.2 Douglas Creek 3PT MKR 3890.0 3895.7 4315.0 4320.7 Black Shale Facies 4550.0 4875.0 4555.7 Castle Peak 4880 7 **Uteland Butte** 4915.0 4920.7 CR 1 5080.0 5085.7 Wasatch 5180.0 5185.7 CR 2 CR 3 5405.0 5410.7 5715.7 5710.0 CR 4 5980.0 5985.7 CR 4A 6120.0 6240.0 6245.7 CR 6

CASING DETAILS


No casing data is available





Start Build 1.50

Start 2496.9 hold at 1149.4 MD



Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 4-36D-47 LC Tribal

 Well:
 4-36D-47 LC Tribal

Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 4-36D-47 LC Tribal

KB @ 6700.0ft (Original Well Elev) KB @ 6700.0ft (Original Well Elev)

True

Minimum Curvature

Project DUCHESNE COUNTY, UT (NAD 27)

Map System: US State Plane 1927 (Exact solution)
Geo Datum: NAD 1927 (NADCON CONUS)

Map Zone: Utah Central 4302

System Datum:

Ground Level

Site 4-36D-47 LC Tribal

Northing: 642,867.11 ft Site Position: Latitude: 40° 5' 42.349 N From: Lat/Long Easting: 2,243,306.04 ft Longitude: 110° 37' 49.001 W **Position Uncertainty:** 0.0 ft Slot Radius: **Grid Convergence:** 0.56 °

Well 4-36D-47 LC Tribal **Well Position** +N/-S 0.0 ft Northing: 642,867.11 ft Latitude: 40° 5' 42.349 N +E/-W 0.0 ft Easting: 2,243,306.04 ft Longitude: 110° 37' 49.001 W **Position Uncertainty** 0.0 ft Wellhead Elevation: ft **Ground Level:** 6,685.0 ft

Wellbore Wellbore #1 Magnetics **Model Name** Sample Date Declination Dip Angle Field Strength (nT) (°) (°) IGRF2010 5/17/2013 11.30 65.68 52,017

Design Design #1 **Audit Notes:** Tie On Depth: Version: Phase: PLAN 0.0 Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (ft) (ft) (ft) (°) 0.0 0.0 0.0 141.69

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
900.0	0.00	0.00	900.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,149.4	3.74	141.69	1,149.2	-6.4	5.0	1.50	1.50	0.00	141.69	
3,646.3	3.74	141.69	3,640.8	-134.2	106.0	0.00	0.00	0.00	0.00	
3,895.7	0.00	0.00	3,890.0	-140.6	111.1	1.50	-1.50	0.00	180.00	4-36D-47 LC Tribal 3
6,245.7	0.00	0.00	6,240.0	-140.6	111.1	0.00	0.00	0.00	0.00	4-36D-47 LC Tribal P

Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 4-36D-47 LC Tribal

 Well:
 4-36D-47 LC Tribal

Wellbore: Wellbore #1

Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 4-36D-47 LC Tribal

KB @ 6700.0ft (Original Well Elev) KB @ 6700.0ft (Original Well Elev)

True

Minimum Curvature

ign:	Design #1								
nned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
Start Build 1		0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
925.0	0.38	141.69	925.0	-0.1	0.1	0.1	1.50	1.50	0.00
Green River	4.50	444.00	4.000.0	4.0	0.0	4.0	4.50	4.50	0.00
1,000.0	1.50	141.69	1,000.0	-1.0	0.8	1.3	1.50	1.50	0.00
1,100.0	3.00	141.69	1,099.9	-4.1	3.2	5.2	1.50	1.50	0.00
1,149.4	3.74	141.69	1,149.2	-6.4	5.0	8.1	1.50	1.50	0.00
	hold at 1149.4 N		1 100 7	0.0	7.4	44.4	0.00	0.00	0.00
1,200.0	3.74	141.69	1,199.7	-9.0	7.1	11.4	0.00	0.00	0.00
1,300.0	3.74	141.69	1,299.5	-14.1	11.1	18.0	0.00	0.00	0.00
1,400.0	3.74	141.69	1,399.3	-19.2	15.2	24.5	0.00	0.00	0.00
1,500.0	3.74	141.69	1,499.1	-24.3	19.2	31.0	0.00	0.00	0.00
1,576.1	3.74	141.69	1,575.0	-28.2	22.3	36.0	0.00	0.00	0.00
Mahogany									
1,600.0	3.74	141.69	1,598.9	-29.5	23.3	37.5	0.00	0.00	0.00
1,700.0	3.74	141.69	1,698.6	-34.6	27.3	44.1	0.00	0.00	0.00
1,800.0	3.74	141.69	1,798.4	-39.7	31.4	50.6	0.00	0.00	0.00
1,900.0	3.74	141.69	1,898.2	-44.8	35.4	57.1	0.00	0.00	0.00
2,000.0	3.74	141.69	1,998.0	-49.9	39.4	63.6	0.00	0.00	0.00
2,100.0	3.74	141.69	2,097.8	-55.1	43.5	70.2	0.00	0.00	0.00
2 200 0	2.74	141.60	2 107 6	-60.2	47.5	76.7	0.00	0.00	0.00
2,200.0 2,300.0	3.74 3.74	141.69 141.69	2,197.6 2,297.4	-65.3	47.5 51.6	76.7 83.2	0.00 0.00	0.00 0.00	0.00 0.00
2,400.0	3.74	141.69	2,397.2	-70.4	55.6	89.7	0.00	0.00	0.00
2,500.0	3.74	141.69	2,496.9	-75.5	59.7	96.3	0.00	0.00	0.00
2,600.0	3.74	141.69	2,596.7	-80.6	63.7	102.8	0.00	0.00	0.00
2,700.0	3.74	141.69	2,696.5	-85.8	67.8	109.3	0.00	0.00	0.00
2,738.6	3.74	141.69	2,735.0	-87.7	69.3	111.8	0.00	0.00	0.00
TGR3	:	444.06	0.700.0	22.2	=1.5	4450	2.22	2.22	2.22
2,800.0	3.74	141.69	2,796.3	-90.9	71.8	115.8	0.00	0.00	0.00
2,900.0	3.74	141.69	2,896.1	-96.0	75.8 70.0	122.3	0.00	0.00	0.00
3,000.0	3.74	141.69	2,995.9	-101.1	79.9	128.9	0.00	0.00	0.00
3,100.0	3.74	141.69	3,095.7	-106.2	83.9	135.4	0.00	0.00	0.00
3,200.0	3.74	141.69	3,195.5	-111.4	88.0	141.9	0.00	0.00	0.00
3,300.0	3.74	141.69	3,295.2	-116.5	92.0	148.4	0.00	0.00	0.00
3,400.0	3.74	141.69	3,395.0	-121.6	96.1	155.0	0.00	0.00	0.00
3,500.0	3.74	141.69	3,494.8	-126.7	100.1	161.5	0.00	0.00	0.00
3,520.2	3.74	141.69	3,515.0	-127.8	100.9	162.8	0.00	0.00	0.00
Douglas Cre	ek								
3,600.0	3.74	141.69	3,594.6	-131.8	104.1	168.0	0.00	0.00	0.00
3,646.3	3.74	141.69	3,640.8	-134.2	106.0	171.0	0.00	0.00	0.00
Start Drop -1	.50								
3,700.0	2.94	141.69	3,694.4	-136.7	108.0	174.2	1.50	-1.50	0.00
3,800.0	1.44	141.69	3,794.3	-139.7	110.3	178.0	1.50	-1.50	0.00
3,895.7	0.00	0.00	3,890.0	-140.6	111.1	179.2	1.50	-1.50	0.00

Planning Report

Database: Compass

Wellbore:

Company: **BILL BARRETT CORP**

Wellbore #1

Project: DUCHESNE COUNTY, UT (NAD 27) 4-36D-47 LC Tribal Site: Well: 4-36D-47 LC Tribal

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well 4-36D-47 LC Tribal

KB @ 6700.0ft (Original Well Elev) KB @ 6700.0ft (Original Well Elev)

True

Minimum Curvature

n:	Design #1								
ed Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
Start 2350.0	nold at 3895.7 M	ID - 3PT MKR							
3,900.0 4,000.0 4,100.0 4,200.0	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	3,894.3 3,994.3 4,094.3 4,194.3	-140.6 -140.6 -140.6 -140.6	111.1 111.1 111.1 111.1	179.2 179.2 179.2 179.2	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
4,300.0 4,320.7	0.00 0.00	0.00 0.00	4,294.3 4,315.0	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00 0.00	0.00 0.00	0.00 0.00
Black Shale	acies								
4,400.0 4,500.0 4,555.7 Castle Peak	0.00 0.00 0.00	0.00 0.00 0.00	4,394.3 4,494.3 4,550.0	-140.6 -140.6 -140.6	111.1 111.1 111.1	179.2 179.2 179.2	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
	0.00	0.00	4.504.0	110.0	444.4	470.0	0.00	0.00	0.00
4,600.0 4,700.0 4,800.0 4,880.7	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	4,594.3 4,694.3 4,794.3 4,875.0	-140.6 -140.6 -140.6 -140.6	111.1 111.1 111.1 111.1	179.2 179.2 179.2 179.2	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
Uteland Butte	•								
4,900.0 4,920.7	0.00	0.00 0.00	4,894.3 4,915.0	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00 0.00	0.00	0.00 0.00
CR 1									
5,000.0 5,085.7	0.00 0.00	0.00 0.00	4,994.3 5,080.0	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00 0.00	0.00 0.00	0.00 0.00
Wasatch									
5,100.0 5,185.7	0.00 0.00	0.00 0.00	5,094.3 5,180.0	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00 0.00	0.00 0.00	0.00 0.00
CR 2									
5,200.0 5,300.0 5,400.0 5,410.7	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	5,194.3 5,294.3 5,394.3 5,405.0	-140.6 -140.6 -140.6 -140.6	111.1 111.1 111.1 111.1	179.2 179.2 179.2 179.2	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
CR 3	0.00	0.00	F 404.2	440.0	444.4	470.0	0.00	0.00	0.00
5,500.0 5,600.0 5,700.0 5,715.7	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	5,494.3 5,594.3 5,694.3 5,710.0	-140.6 -140.6 -140.6 -140.6	111.1 111.1 111.1 111.1	179.2 179.2 179.2 179.2	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
CR 4									
5,800.0 5,900.0	0.00 0.00	0.00 0.00	5,794.3 5,894.3	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00 0.00	0.00 0.00	0.00 0.00
5,985.7	0.00	0.00	5,980.0	-140.6	111.1	179.2	0.00	0.00	0.00
CR 4A 6,000.0 6,100.0 6,125.7	0.00 0.00 0.00	0.00 0.00 0.00	5,994.3 6,094.3 6,120.0	-140.6 -140.6 -140.6	111.1 111.1 111.1	179.2 179.2 179.2	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
CR 5									
6,200.0 6,245.7	0.00	0.00 0.00	6,194.3 6,240.0	-140.6 -140.6	111.1 111.1	179.2 179.2	0.00	0.00 0.00	0.00 0.00
TD at 6245.7			,						

Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 4-36D-47 LC Tribal

 Well:
 4-36D-47 LC Tribal

Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 4-36D-47 LC Tribal

KB @ 6700.0ft (Original Well Elev) KB @ 6700.0ft (Original Well Elev)

True

Minimum Curvature

Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
4-36D-47 LC Tribal 3PT - plan hits target - Rectangle (sides V	0.00 V200.0 H200.0	0.00 D2,350.0)	3,890.0	-140.6	111.1	642,727.60	2,243,418.46	40° 5' 40.960 N	110° 37' 47.572 W
4-36D-47 LC Tribal PBH - plan hits target - Rectangle (sides V		0.00 () D0.0)	6,240.0	-140.6	111.1	642,727.60	2,243,418.46	40° 5' 40.960 N	110° 37' 47.572 W

ormations						
	Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
	925.0	925.0	Green River		0.00	
	1,576.1	1,575.0	Mahogany		0.00	
	2,738.6	2,735.0	TGR3		0.00	
	3,520.2	3,515.0	Douglas Creek		0.00	
	3,895.7	3,890.0	3PT MKR		0.00	
	4,320.7	4,315.0	Black Shale Facies		0.00	
	4,555.7	4,550.0	Castle Peak		0.00	
	4,880.7	4,875.0	Uteland Butte		0.00	
	4,920.7	4,915.0	CR 1		0.00	
	5,085.7	5,080.0	Wasatch		0.00	
	5,185.7	5,180.0	CR 2		0.00	
	5,410.7	5,405.0	CR 3		0.00	
	5,715.7	5,710.0	CR 4		0.00	
	5,985.7	5,980.0	CR 4A		0.00	
	6,125.7	6,120.0	CR 5		0.00	
	6,245.7	6,240.0	CR 6		0.00	

Plan Annotatio	ns				
	Measured	Vertical	Local Coord	dinates	
	Depth (ft)	Depth (ft)	+N/-S (ft)	+E/-W (ft)	Comment
	900.0	900.0	0.0	0.0	Start Build 1.50
	1,149.4	1,149.2	-6.4	5.0	Start 2496.9 hold at 1149.4 MD
	3,646.3	3,640.8	-134.2	106.0	Start Drop -1.50
	3,895.7	3,890.0	-140.6	111.1	Start 2350.0 hold at 3895.7 MD
	6,245.7	6,240.0	-140.6	111.1	TD at 6245.7

SURFACE USE PLAN

BILL BARRETT CORPORATION

LC Tribal 4-36D-47 Well Pad

NW NW, 669' FNL and 699' FWL, Sec. 36, T4S-R7W (surface hole) NW NW, 810' FNL and 810' FWL, Sec. 36, T4S-R7W (bottom hole) Duchesne County, Utah

The onsite inspection for this pad occurred on August 7, 2012. This is a new pad with one proposed well. Plat changes and site specific stipulations requested at the onsite are reflected within this APD and summarized below.

- 1) Shorten trailer side of the pad (pad corners 2 to 8) to 135 feet;
- 2) Cut off corners 6 & 2 and round corner 8 to minimize fill slopes;
- 3) Relocate topsoil from corners 2 & 3 to corners 3 & 4;
- 4) Insure pad fill slopes do not enter the Dry Canyon drainage;
- 5) Divert surface run-off around the NW corner of the pad (Corner 4);
- 6) Install a 24-inch culvert at the beginning of the road re-route;
- 7) Relocate pipeline to the east side of the road to provide additional buffer to cultural resources (historic cabin area).

The excavation contractor would be provided with an approved copy of the surface use plan of operations before initiating construction.

1. Existing Roads:

- a. The proposed well site is located 18.6 miles southwest of Duchesne, Utah. Maps and directions reflecting the route to the proposed well site are included (see Topographic maps A and B).
- b. The existing State Highway 40 would be utilized from Duchesne for 8.3 miles to the existing Duchesne County maintained Strawberry River Road that would be utilized for 7.0 miles to the existing Dry Canyon Access Road that provides access to the planned new access road.
- c. Project roads would require routine year-round maintenance to provide year-round access. Maintenance would include inspections, reduction of ruts and holes, maintenance to keep water off the road, replacement of surfacing materials, and clearing of sediment blocking ditches and culverts. Should snow removal become necessary, roads would be cleared with a motor grader and snow would be stored along the down gradient side to prohibit runoff onto the road. Aggregate would be used as necessary to maintain a solid running surface and minimize dust generation.
- d. Vehicle operators would obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions. Travel would be limited to the existing access roads and proposed access road.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- e. The use of roads under State and Duchesne County Road Department maintenance are necessary to access the project area with no improvements proposed. No encroachment or pipeline crossing permits are required.
- f. All existing roads would be maintained and kept in good repair during all phases of operation.

2. Planned Access Road:

- a. Approximately 1,080 feet of existing two-track upgrade and new road re-route trending southwest is planned from the proposed LC Fee 13-25D-47 pad. The proposed LC Fee 13-25D-47 access road continues an additional 16,104 feet (3.1 miles) to the existing Duchesne County maintained Strawberry River access road (see Topographic Map B). The proposed access road crosses entirely Ute Indian Tribe surface.
- b. The planned access road would be constructed to a 30-foot ROW width with an 18-foot travel surface. See section 12.d. below for disturbance estimates.
- c. New road construction and improvements of existing roads would typically require the use of motor graders, crawler tractors, 10-yard end dump trucks, and water trucks. The standard methodology for building new roads involves the use of a crawler tractor or track hoe to windrow the vegetation to one side of the road corridor, remove topsoil to the opposing side of the corridor, and rough-in the roadway. This is followed by a grader or bulldozer to establish barrow ditches and crown the road surface. Where culverts are required, a track hoe or backhoe would trench the road and install the culverts. Some hand labor would be required when installing and armoring culverts. Road base or gravel in some instances would be necessary and would be hauled in and a grader used to smooth the running surface.
- d. The proposed road would be constructed to facilitate drainage, control erosion and minimize visual impacts by following natural contours where practical. No unnecessary side-casting of material would occur on steep slopes.
- e. A maximum grade of 10% would be maintained throughout the project with minimum cuts and fills, as necessary, to access the well.
- f. Excess rock from construction of the pad may be used for surfacing of the access road if necessary. Any additional aggregate necessary would be obtained from private or State of Utah lands in conformance with applicable regulations. Aggregate would be of sufficient size, type, and amount to allow all weather access and alleviate dust.
- g. Where topsoil removal is necessary, it would be windrowed (i.e. stockpiled/accumulated along the edge of the ROW and in a low row/pile parallel with the ROW) and re-spread over the disturbed area after construction and backfilling are completed. Vegetation removed from the disturbed area

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

would also be re-spread to provide protection, nutrient recycling, and a seed source for reclamation.

- h. Turnouts are not proposed.
- One 24-inch culvert along the proposed road and no low-water crossings are anticipated. Adequate drainage structures, where necessary, would be incorporated into the remainder of the road to prevent soil erosion and accommodate all-weather traffic.
- j. No gates or cattle guards are anticipated at this time.
- k. Surface disturbance and vehicular travel would be limited to the approved location access road. Adequate signs would be posted, as necessary, to warn the public of project related traffic.
- All access roads and surface disturbing activities would conform to the
 appropriate standard, **no higher than necessary**, to accommodate their intended
 function adequately as outlined in the Bureau of Land Management and Forest
 Service publication: <u>Surface Operating Standards for Oil and Gas Exploration</u>
 and <u>Development</u>, Fourth Edition Revised 2007.
- m. The operator would be responsible for all maintenance needs of the new access road.

3. <u>Location of Existing Wells (see One-Mile Radius Map):</u>

a. Following is a list of wells with surface hole locations within a one-mile radius of the proposed pad:

i.	water wells	none
ii.	injection wells	none
iii.	disposal wells	none
iv.	drilling wells	none
v.	temp shut-in wells	none
vi.	producing wells	none
vii.	abandoned wells	one

4. <u>Location of Production Facilities</u>

a. Surface facilities for a single well pad would consist of a wellhead, separator, gas meter, combustor, (1) 500 gal methanol tank, (1) 500 glycol tank, (3) 500 bbl oil tanks, (1) 500 bbl water tank, (1) 400 bbl emergency tank, (1) 1000 gal propane tank, a pumping unit or Roto-flex unit or ESP or gas lift unit, electrical or with a natural gas or diesel fired motor, solar panels, solar chemical and methanol pumps and one trace pump, and if necessary power lines. See attached proposed facility diagram. Additional equipment may be added when more than one well is drilled on each pad.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- b. Most wells would be fitted with a pump jack or Roto-flex unit or ESP or gas lift to assist liquid production. The prime mover for pump jacks or Roto-flex units would be small (100 horsepower or less), electric motor or natural gas or diesel fired internal combustion engines. If a gas lift is installed, it would be set on a 10 ft x 25 ft pad and the prime mover would be a natural gas-fired internal combustion engine rated at 200 horsepower or less or an electric compressor of similar horsepower powered by electricity.
- c. The tank battery would be surrounded by a secondary containment berm of sufficient capacity to contain 1.1 times the entire capacity of the largest single tank and sufficient freeboard to contain precipitation. All loading lines and valves would be placed inside the berm surrounding the tank battery or would utilize catchment basins to contain spills. All liquid hydrocarbon production and measurement shall conform to the provisions of 43 CFR 3162.7-2 and Onshore Oil and Gas Order No. 4 for the measurement of oil.
- d. Gas meter run(s) would be constructed and located on lease within 500 feet of the wellheads. Meter runs would be housed and/or fenced. As practicably feasible, meters would be equipped with remote telemetry monitoring systems. All gas production and measurement shall comply with the provisions of 43 CFR 3162.7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3.
- e. A combustor may be installed at this location for control of associated condensate tank emissions. A combustor ranges from 24 inches to 48 inches wide and is approximately 27 ft tall. Combustor placement would be on existing disturbance.
- f. Approximately 1,083 feet of pipeline corridor (see Topographic Map C) containing up to three lines (one gas pipeline up to 8 inch in diameter, one water line up to 4 inch in diameter and one residue line up to 4 inch in diameter) is proposed trending northeast to the proposed LC Fee 13-25D-47 pipeline corridor. The proposed pipeline continues from the proposed LC Fee 13-25D-47 pipeline approximately 3.1 miles to the existing BBC maintained 1-13-47 BTR pipeline corridor. Pipelines would be constructed of steel, polyethylene or fiberglass and would connect to the proposed pipeline servicing nearby BBC wells. The pipeline crosses entirely Ute Tribe surface.
- g. The new segment of gas pipeline would be surface laid or buried within a 30 foot wide pipeline corridor adjacent to the proposed access road. Approval to bury pipelines would be obtained from the appropriate surface owner(s). See 12.d below for disturbance estimates.
- h. Construction of the ROW would temporarily utilize the 30 foot disturbed width for the road for a total disturbed width of 60 foot for the road and pipeline corridors. The use of the proposed well site and access roads would facilitate the staging of the pipeline construction.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- Pipeline construction methods and practices would be planned and conducted by BBC with the objective of enhancing reclamation and fostering the reestablishment of the native plant community.
- j. All permanent above-ground structures would be painted a flat, non-reflective color, such as Beetle Green, to match the standard environmental colors. All facilities would be painted the designated color at the time of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.
- k. Site security guidelines identified in 43 CFR 3162.7-5 and Onshore Oil and Gas Order No. 3 would be adhered to. Any modifications to proposed facilities would be reflected in the site security diagram submitted.
- 1. The site would require periodic maintenance to ensure that drainages are kept open and free of debris, and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.

5. <u>Location and Type of Water Supply:</u>

a. Water for the drilling and completion would be trucked from any of the following locations:

Water Right No. and Application or Change No.	Applicant	Allocation	Date	Point of Diversion	Source
43-180	Duchesne City	5.0 cfs	8/13/2004	Knight	Duchesne
	Water Service			Diversion Dam	River
	District				
43-1202, Change a13837	Myton City	5.49 cfr and	3/21/1986	Knight	Duchesne
		3967 acre feet		Diversion Dam	River
43-10444, Appln A57477	Duchesne	2.0 cfs	1994	Ditch at	Cow Canyon
	County Upper			Source	Spring
	Country Water				
43-1273, Appln A17462	J.J.N.P.	7.0 cfs	1946	Strawberry	Strawberry
	Company			River	River
43-1273, Appln t36590	J.J.N.P.	4.0 cfs	6/03/2010	Strawberry	Strawberry
	Company			River	River
43-2505, Appln t37379	McKinnon	1.3 cfs	4/28/2011	Pumped from	Water Canyon
	Ranch			Sec, 17, T4S,	Lake
	Properties, LC			R6W	
43-12415, Change A17215a	Peatross	1.89 cfs	09/2011	Dugout Pond	Strawberry
	Ranch, LLC				River

b. No new water well is proposed with this application.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- c. Should additional water sources be pursued they would be properly permitted through the State of Utah Division of Water Rights.
- d. Water use would vary in accordance with the formations to be drilled but would be up to approximately 5.41 acre feet for drilling and completion operations.

6. Source of Construction Material:

- a. The use of materials would conform to 43 CFR 3610.2-3.
- b. No construction materials would be removed from the lease or EDA area.
- c. If any additional gravel is required, it would be obtained from a local supplier having a permitted source of materials within the general area.

7. Methods of Handling Waste Disposal:

- a. All wastes associated with this application would be contained and disposed of utilizing approved facilities.
- b. The reserve pit would be constructed so as not to leak, break or allow any discharge.
- c. The reserve would be lined with 12 mil (minimum) thickness polyethylene nylon reinforced liner material. The liner(s) would overlay straw, dirt and/or bentonite if rock is encountered during excavation. The liner would overlap the pit walls and be covered with dirt and/or rocks to hold them in place. No trash, scrap pipe, or other materials that could puncture the liner would be discarded in the pit. A minimum of two feet of free board would be maintained between the maximum fluid level and the top of the reserve pit at all times.
- d. To deter livestock from entering the pit, the three sides exterior to the location would be fenced before drilling starts. Following the conclusion of drilling and completion activities, the fourth side would also be fenced.
- e. Drill cuttings would be contained in the pit and buried on-site for a period not to exceed six months, weather permitting
- f. Produced fluids from the well other than water would be decanted into steel test tank(s) until such time as construction of production facilities is completed. Any oil that may be accumulated would be transferred to a permanent production tank. Produced water may be used in further drilling and completion activities, evaporated in the pit, or would be hauled to one of the state-approved disposal facilities below:

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

Disposal Facilities

- 1. RNI Industries, Inc. Pleasant Valley Disposal Pits, Sec. 25, 26, 35 & 36, T4S-R3W
- 2. Pro Water LLC Blue Bench 13-1 Disposal Well (43-013-30971) NENE, Sec. 13, T3S-R5W
- 3. RN Industries, Inc. Bluebell Disposal Ponds, Sec. 2, 4 & 9, T2S-R2W
- 4. Water Disposal, Inc. Harmston 1-32-A1 Disposal Well (43-013-30224), UTR #00707, Sec. 32, T1S-R1W
- 5. Unified Water Pits Sec. 31, T2S-R4W
- 6. Iowa Tank Line Pits 8500 BLM Fence Road, Pleasant Valley
- 7. Western Water Solutions Sand Pass Ranch, Sections 9 and 10, T4S-R1W, permit #WD-01-2011
- g. Any salts and/or chemicals, which are an integral part of the drilling system, would be disposed of in the same manner as the drilling fluid.
- h. Any spills of oil, condensate, produced or frac water, drilling fluids, or other potentially deleterious substances would be recovered and either returned to its origin or disposed of at an approved disposal site, most likely in Duchesne, Utah.
- i. Chemicals on the EPA's Consolidated List of Chemicals subject to reporting under Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) may be used or stored in quantities over reportable quantities. In the course of drilling, BBC could potentially store and use diesel fuel, sand (silica), hydrochloric acid, and CO₂ gas, all described as hazardous substances in 40 CFR Part 302, Section 302.4, in quantities exceeding 10,000 pounds. In addition, natural gas condensate and crude oil and methanol may be stored or used in reportable quantities. Small quantities of retail products (paint/spray paints, solvents {e.g., WD-40}, and lubrication oil) containing non-reportable volumes of hazardous substances may be stored and used on site at any time. No extremely hazardous substances, as defined in 40 CFR 355, would be used, produced, stored, transported or disposed of in association with the drilling, testing or completion of the wells.
- j. Portable toilets and trash containers would be located onsite during drilling and completion operations. A commercial supplier would install and maintain portable toilets and equipment and would be responsible for removing sanitary waste. Sanitary waste facilities (i.e. toilet holding tanks) would be regularly pumped and their contents disposed of at approved sewage disposal facilities in Duchesne, and/or Uintah Counties, in accordance with applicable rules and regulations regarding sewage treatment and disposal. Accumulated trash and nonflammable waste materials would be hauled to an approved landfill once a week or as often as necessary. All debris and waste materials not contained in the trash containers would be cleaned up, removed from the construction ROW, well pad, or worker housing location, and disposed of at an approved landfill. Trash would be cleaned up everyday.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- k. Sanitary waste equipment and trash bins would be removed from the Project Area upon completion of access road or pipeline construction; following drilling and completion operations at an individual well pad; when worker housing is no longer needed; or as required.
- 1. A flare pit may be constructed a minimum of 110' from the wellhead(s) and may be used during completion work. In the event a flare pit proves to be unworkable, a temporary flare stack or open top tank would be installed. BBC would flow back as much fluid and gas as possible into pressurized vessels, separating the fluids from the gas. In some instances, due to the completion fluids utilized within the Project Area, it is not feasible to direct the flow stream from the wellbore through pressurized vessels. In such instances BBC proposes to direct the flow to the open top tanks until flow through the pressurized vessels is feasible. At which point the fluid would either be returned to the reserve pit or placed into a tank(s). The gas would be directed to the flare pit, flare stack (each with a constant source of ignition), or may be directed into the sales pipeline.
- m. Hydrocarbons would be removed from the reserve pit would as soon as practical. In the event immediate removal is not practical, the reserve pit would be flagged overhead or covered with wire or plastic mesh to protect migrating birds.

8. Ancillary Facilities:

- a. Garbage containers and portable toilets would be located on the well pad.
- b. On well pads where active drilling and completion is occurring, temporary housing would be provided on location for the well pad supervisor, geologist, tool pusher, and others that are required to be on location at all times. The well pad could include up to five single wide mobile homes or fifth wheel campers/trailers.
- c. A surface powerline corridor is not proposed with this application but may be applied for in the future.

9. Well Site Layout:

- a. The well would be properly identified in accordance with 43 CFR 3162.6.
- b. The pad layout, cross section diagrams and rig layout are enclosed (see Figures 1 and 2).
- c. The pad and road designs are consistent with industry specifications.
- d. The pad has been staked at its maximum size of 400 feet x 245 feet with an inboard reserve pit size of 235 feet x 70 feet x 8 feet deep. See section 12.d below for disturbance estimates.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- e. Within the approved well pad location, a crawler tractor would strip whatever topsoil is present and stockpile it along the edge of the well pad for use during reclamation. Vegetation would be distributed along the sides of the well pad.
- f. Fill from pit excavation would be stockpiled along the edge of the pit and the adjacent edge of the well pad.
- g. Use of erosion control measures, including proper grading to minimize slopes, diversion terraces and ditches, mulching, terracing, riprap, fiber matting, temporary sediment traps, and broad-based drainage dips or low water crossings would be employed by BBC as necessary and appropriate to minimize erosion and surface runoff during well pad construction and operation. Cut and fill slopes would be constructed such that stability would be maintained for the life of the activity.
- h. All cut and fill slopes would be such that stability can be maintained for the life of the activity.
- i. Diversion ditches would be constructed, if necessary, around the well site to prevent surface waters from entering the well site area.
- j. Water application may be implemented if necessary to minimize the amount of fugitive dust.
- k. All surface disturbing activities would be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.

10. Plan for Restoration of the Surface:

- a. A site specific reclamation plan would be submitted, if requested, within 90 days of location construction to the surface managing agency.
- b. Site reclamation would be accomplished for portions of the well pad not required for the continued operation of the well on this pad within six months of completion, weather permitting.
- c. The operator would control noxious weeds along access road use authorizations and well site by spraying or mechanical removal, according to the Utah Noxious Weed Act and as set forth in the approved surface damage agreements.
- d. Rat and mouse holes would be filled and compacted from bottom to top immediately upon release of the drilling rig from location. Upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1. The reserve pit would be allowed to dry prior to the commencement of backfilling work. No attempts would be made to backfill the reserve pit until it is free of standing water. Once dry, the liner would be torn and perforated before backfilling.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

- e. The reserve pit and that portion of the location not needed for production facilities/operations would be recontoured to the approximate natural contours. Areas not used for production purposes would be backfilled and blended into the surrounding terrain, reseeded and erosion control measures installed. Mulching, erosion control measures and fertilization may be required to achieve acceptable stabilization. Back slopes and fore slopes would be reduced as practical and scarified with the contour. The reserved topsoil would be evenly distributed over the slopes and scarified along the contour. Slopes would be seeded with the Ute Tribe specified seed mix.
- f. Topsoil salvaged from the drill site and stored for more than one year would be placed at the location indicated on the well site layout drawing and graded to a depth optimum to maintain topsoil viability, seeded with the Ute Tribe prescribed seed mixture and covered with mulch for protection from wind and water erosion and to discourage the invasion of weeds.

11. Surface and Mineral Ownership:

- a. Surface ownership Ute Indian Tribe 988 South 7500 East; Ft. Duchesne, Utah 84026; 435-725-4982.
- b. Mineral ownership Ute Indian Tribe 988 South 7500 East; Ft. Duchesne, Utah 84026; 435-725-4982.

12. Other Information:

- a. Montgomery Archeological Consultants has conducted a Class III archeological survey. A copy of the report has been submitted under separate cover to the appropriate agencies by Montgomery as report 12-082 (U-12-MQ-0289i) dated April 27, 2012.
- b. BBC would require that their personnel, contractors, and subcontractors to comply with Federal regulations intended to protect archeological and cultural resources.
- c. Project personnel and contractors would be educated on and subject to the following requirements:
 - No dogs or firearms within the Project Area.
 - No littering within the Project Area.
 - Smoking within the Project Area would only be allowed in off-operator active locations or in specifically designated smoking areas. All cigarette butts would be placed in appropriate containers and not thrown on the ground or out windows of vehicles; personnel and contractors would abide by all fire restriction orders.
 - Campfires or uncontained fires of any kind would be prohibited.
 - Portable generators used in the Project Area would have spark arrestors.

Bill Barrett Corporation Surface Use Plan LC Tribal 4-36D-47 Well Pad Duchesne County, UT

d. Disturbance estimates:

Approximate Acreage Disturbances

 Well Pad
 5.346 acres

 Access
 1,080 feet
 0.706 acres

 Pipeline
 1,082 feet
 0.709 acres

Total 6.761 acres

OPERATOR CERTIFICATION

Certification:

I hereby certify that I, or someone under my direction supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein would be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application and that bond coverage is provided under Bill Barrett Corporations federal nationwide bond. These statements are subject to the provisions of 18 U.S.C. 1001 for the filings of false statements.

Executed this

Name:

Venessa Langmacher

Position Title:

Senior Permit Analyst

Address: 1099 18th Street, Suite 2300, Denver, CO 80202

Telephone: 303-312-8172


E-mail: vlangmacher@billbarrettcorp.com
Field Representative Kary Eldredge / Bill Barrett Corporation
Address: 1820 W. Highway 40, Roosevelt, UT 84066
Telephone: 435-725-3515 (office); 435-724-6789 (mobile)

E-mail: keldredge@billbarrettcorp.com

Venessa Langmacher, Senior Permit Analyst


BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. BLOWOUT PREVENTER



BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. CHOKE MANIFOLD





May 22, 2013

Ms. Diana Mason – Petroleum Technician State of Utah Division of Oil, Gas and Mining 1594 West North Temple, Suite 1210 P. O. Box 145801 Salt Lake City, Utah 84114-5801

Re: Directional Drilling R649-3-11

Lake Canyon Area #4-36D-47 LC Tribal Well

Surface: 669' FNL & 699' FWL, NWNW, 36-T4S-R7W, USM Bottom Hole: 810' FNL & 810' FWL, NWNW, 36-T4S-R7W, USM

Duchesne County, Utah

Dear Ms. Mason,

Pursuant to the filing of Bill Barrett Corporation's ("BBC") Application for Permit to Drill the above referenced well, we hereby submit this letter in accordance with Oil & Gas Conservation Rules R649-2, R649-3, R649-10 and R649-11, pertaining to the Location and Siting of Wells.

- The proposed location is within our Lake Canyon Area.
- BBC is permitting this well as a directional well in order to minimize surface disturbance. By locating the well at the surface location and directionally drilling from this location, BBC will be able to utilize the existing road and pipelines in the area.
- The well will be drilled under an Exploration and Development Agreement between the Ute Indian Tribe and Ute Distribution Corporation. Crescent Point Energy U.S. Corp owns a right to participate in this well.
- BBC certifies that it is the working interest owner of all lands within 460 feet of the proposed well location, and together with Crescent Point Energy U.S. Corp, we own 100% of the working interest in these lands.


Based on the information provided, BBC requests that the permit be granted pursuant to R649-3-11. Should you have any questions or need further information, please contact me at 303-312-8544.

Sincerely,

Venessa Langmacher Senior Permit Analyst


1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303.293.9100
F 303.291.0420

RECEIVED: May 22, 2013




FILL


13,830 CU. YDS.




UINTAH ENGINEERING & LAND SURVEYING

85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017







API Well Number: 43013521860000

WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 5/22/2013 **API NO. ASSIGNED:** 43013521860000

WELL NAME: LC Tribal 4-36D-47

OPERATOR: BILL BARRETT CORP (N2165) **PHONE NUMBER:** 303 312-8172

CONTACT: Venessa Langmacher

PROPOSED LOCATION: NWNW 36 040S 070W Permit Tech Review:

SURFACE: 0669 FNL 0699 FWL Engineering Review:

BOTTOM: 0810 FNL 0810 FWL Geology Review:

COUNTY: DUCHESNE

LATITUDE: 40.09494 LONGITUDE: -110.63085

UTM SURF EASTINGS: 531467.00 **NORTHINGS:** 4438360.00

FIELD NAME: UNDESIGNATED
LEASE TYPE: 2 - Indian

LEASE NUMBER: 20G0005500 **PROPOSED PRODUCING FORMATION(S):** GREEN RIVER(LWR)-WASATCH

SURFACE OWNER: 2 - Indian COALBED METHANE: NO

RECEIVED AND/OR REVIEWED: LOCATION AND SITING: ✓ PLAT R649-2-3. Bond: INDIAN - LPM8874725 Unit: **Potash** R649-3-2. General Oil Shale 190-5 R649-3-3. Exception Oil Shale 190-3 Oil Shale 190-13 **Drilling Unit** Board Cause No: Cause 139-87 Water Permit: 43-180 Effective Date: 12/6/2011 **RDCC Review:** Siting: 4 Prod LGRRV-WSTC Wells Fee Surface Agreement


Intent to Commingle R649-3-11. Directional Drill

Commingling Approved

Comments: Presite Completed

Stipulations: 4 - Federal Approval - dmason

15 - Directional - dmason



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: LC Tribal 4-36D-47 **API Well Number:** 43013521860000

Lease Number: 20G0005500

Surface Owner: INDIAN Approval Date: 5/23/2013

Issued to:

BILL BARRETT CORP, 1099 18th Street Ste 2300, Denver, CO 80202

Authority:

Pursuant to Utah Code Ann. 40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 139-87. The expected producing formation or pool is the GREEN RIVER(LWR)-WASATCH Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

• Within 24 hours following the spudding of the well - contact Carol Daniels at 801-538-5284

(please leave a voicemail message if not available)

OR

submit an electronic sundry notice (pre-registration required) via the Utah Oil &

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) due within 5 days of spudding the well
- Monthly Status Report (Form 9) due by 5th day of the following calendar month
 - Requests to Change Plans (Form 9) due prior to implementation
 - Written Notice of Emergency Changes (Form 9) due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) due prior to implementation
 - Report of Water Encountered (Form 7) due within 30 days after completion
- Well Completion Report (Form 8) due within 30 days after completion or plugging

Approved By:

For John Rogers Associate Director, Oil & Gas Sundry Number: 61987 API Well Number: 43013521860000

	STATE OF UTAH		FORM 9
ı	DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING	3	5.LEASE DESIGNATION AND SERIAL NUMBER: 2OG0005500
SUNDR	RY NOTICES AND REPORTS ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
	posals to drill new wells, significantly deep reenter plugged wells, or to drill horizontal n for such proposals.		7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: LC Tribal 4-36D-47
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NUMBER: 43013521860000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300		DNE NUMBER: 312-8134 Ext	9. FIELD and POOL or WILDCAT: UNDESIGNATED
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0669 FNL 0699 FWL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 36 Township: 04.0S Range: 07.0W Meridia	n: U	STATE: UTAH
11. CHECI	K APPROPRIATE BOXES TO INDICATE N	IATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
5/23/2015	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	New construction
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	U TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
Report Date:	WILDCAT WELL DETERMINATION	OTHER	OTHER-
40 DECODINE DRODOGED OF		office of Lot 12 to 12 t	omen.
	completed operations. Clearly show all peruest a one year extension for A		Approved by the
220 110100) 109	5/23/2015	T B Willow Oxpired	UManchivitic2005
			Oil, Gas and Mining
			Date:
			By: Laggill
			35
NAME (PLEASE PRINT) Brady Riley	PHONE NUMBER 303 312-8115	TITLE Permit Analyst	
SIGNATURE		DATE	
N/A		3/31/2015	

Sundry Number: 61987 API Well Number: 43013521860000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013521860000

API: 43013521860000 **Well Name:** LC Tribal 4-36D-47

Location: 0669 FNL 0699 FWL QTR NWNW SEC 36 TWNP 040S RNG 070W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 5/23/2013

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? Yes No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
natural Produ Bilov Pata: 2/21/2015

Signature: Brady Riley Date: 3/31/2015

Title: Permit Analyst Representing: BILL BARRETT CORP

Form 3160-5 (August 2007)

HEUEIVED

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT JAN 0 4 2016

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

5. Lease Serial No. 1420H625500

SUNDRY NO	TICES AND REPORTS ON WELLS	
Do not use this fo abandoned well. U	orm for proposals to only or the relater and lise form 3160-3 (APD) To such proposals.	

ertify that the applicant holds legal or equ	itable title to those rights in the	not warrant or subject lease Office	ERNAL FIELD OFFICE	90 72 83
Approved By	<u> </u>	Title Land		JAN 1 2 2016
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE USE	
Signature (Electronic S	iubmission)	Date 01/04/2	2016	
Name (Printed/Typed) BRADY RI	ILEY_	Title PERMI	TANALYST	
Comr	Electronic Submission #3 For BILL BARF mitted to AFMSS for proces	RETT CORPORATION, sent to ssing by ROBIN R. HANSEN or	ell Information System I the Vernal n 01/06/2016 (16RRH0054SE)	
14. I hereby certify that the foregoing is	true and correct	<u> </u>		·
CONDITIONS OF APPE	TOVAL AT INCHED		RECL	
CONDITIONS OF ADDE	OOVAL ATTACHED		PET	
			E.S	
			GEOL	
APB- 2/4/14			ENG. RHI	1/16
BBC hereby request a two year	• '	4/2018.		OFFICE
Attach the Bond under which the wor following completion of the involved testing has been completed. Final At	rk will be performed or provide l operations. If the operation res pandonment Notices shall be file	the Bond No. on file with BLM/BL sults in a multiple completion or rec	 A. Required subsequent reports shall completion in a new interval, a Form 	ll be filed within 30 days 3160-4 shall be filed once
13. Describe Proposed or Completed Ope	eration (clearly state all pertinen	t details, including estimated starting	ng date of any proposed work and ap	proximate duration thereof
Solution of Internt Alter Casing Fracture Treat Reclamation Well				
- · ·	l ·	_		Other Change to Original A
	_		_ `	Water Shut-Off Well Integrity
TYPE OF SUBMISSION	D A sidire			D Water Short Off
	ROPKIATE BUX(ES) TO			nek data
12 CITECU ADDI	DODDIATE BOVES TO			UED DATA
			DUCHESNE	ECOUNTY, UT
	T., R., M., or Survey Description,	ΙΔΝ 2.5 2016	11. County or Par	rish, and State
1099 18TH STREET SUITE 2	2300	3b. Phone No. (include are code) Ph: 303-RECEIVED	e) 10. Field and Pool UNDESIGN	
2. Name of Operator BILL BARRETT CORPORAT		barrettcorp.com	43-013-5218	86-00-X1
☑ Oil Well ☐ Gas Well ☐ Ot			LC TRIBAL 4	
·			8 Well Name and	No
abandoned we	ell. Use form 3160-3 (AP	Dinsut property	6. If Indian, Allow	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Revisions to Operator-Submitted EC Data for Sundry Notice #327627

Operator Submitted

BLM Revised (AFMSS)

Sundry Type:

OTHER

NOI

1420H625500

APDCH NOI

1420H625500

Agreement:

Lease:

Operator:

BILL BARRETT CORPORATION 1099 18TH STREET SUITE 2300 DENVER, CO 80202 Ph: 303-293-9100

BILL BARRETT CORPORATION 1099 18TH STREET SUITE 2300 DENVER, CO 80202 Ph: 303.312.8546

BRADY RILEY PERMIT ANALYST E-Mail: briley@billbarrettcorp.com

Admin Contact:

BRADY RILEY PERMIT ANALYST E-Mail: briley@billbarrettcorp.com

Ph: 303-312-8115

Ph: 303-312-8115

Tech Contact:

BRADY RILEY PERMIT ANALYST

E-Mail: briley@billbarrettcorp.com

Ph: 303-312-8115

BRADY RILEY PERMIT ANALYST E-Mail: briley@billbarrettcorp.com

Ph: 303-312-8115

Location:

State:

County:

UT DUCHESNE

Field/Pool:

ALTAMONT

Well/Facility:

LC TRIBAL 4-36D-47 Sec 36 T4S R7W Mer UBM NWNW 669FNL 699FWL

UT DUCHESNE

UNDESIGNATED

LC TRIBAL 4-36D-47 Sec 36 T4S R7W NWNW 669FNL 699FWL 40.095056 N Lat, 110.630989 W Lon

CONDITIONS OF APPROVAL

Bill Barrett Corporation

Notice of Intent APD Extension

Lease:

1420H625500

Well:

LC Tribal 4-36D-47

Location:

NWNW Sec 36-T4S-R7W

An extension for the referenced APD is granted with the following conditions:

- 1. The extension and APD shall expire on 02/04/2018.
- 2. No other extensions shall be granted.

If you have any other questions concerning this matter, please contact Robin L Hansen of this office at (435) 781-2777

Sundry Number: 70216 API Well Number: 43013521860000

	STATE OF UTAH		FORM 9
ı	DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING	3	5.LEASE DESIGNATION AND SERIAL NUMBER: 20G0005500
	Y NOTICES AND REPORTS ON	_	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
	posals to drill new wells, significantly deep reenter plugged wells, or to drill horizontal n for such proposals.		7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: LC Tribal 4-36D-47
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NUMBER: 43013521860000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300		DNE NUMBER: 312-8134 Ext	9. FIELD and POOL or WILDCAT: UNDESIGNATED
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0669 FNL 0699 FWL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH	HP, RANGE, MERIDIAN: 36 Township: 04.0S Range: 07.0W Meridia	n: U	STATE: UTAH
11. CHECI	K APPROPRIATE BOXES TO INDICATE N	ATURE OF NOTICE, REPOF	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
~	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
5/23/2017	☐ CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
Date of Work Completion:		PLUG AND ABANDON	PLUG BACK
		RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:			
Date of opau.		SIDETRACK TO REPAIR WELL	L TEMPORARY ABANDON
		VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
	WILDCAT WELL DETERMINATION	OTHER	OTHER:
	COMPLETED OPERATIONS. Clearly show all peuest a one year extension for A		lepths, volumes, etc. Approved by the Wanchiଡ଼ିଆ ପ୍ରତିତି Oil, Gas and Mining
			Date:
			By: Dangelle
NAME (PLEASE PRINT) Brady Riley	PHONE NUMBER 303 312-8115	TITLE Permit Analyst	
SIGNATURE		DATE	
N/A		3/2/2016	

Sundry Number: 70216 API Well Number: 43013521860000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013521860000

API: 43013521860000 Well Name: LC Tribal 4-36D-47

Location: 0669 FNL 0699 FWL QTR NWNW SEC 36 TWNP 040S RNG 070W MER U

Company Permit Issued to: BILL BARRETT CORP

Date Original Permit Issued: 5/23/2013

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? Yes No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
nature: Brady Biley Date: 3/2/2016

Signature: Brady Riley **Date:** 3/2/2016

Title: Permit Analyst Representing: BILL BARRETT CORP

Division of Oil, Gas and Mining

Operator Change/Name Change Worksheet-for State use only

Effective Date:

11/1/2016

FORMER OPERATOR:	NEW OPERATOR:
Bill Barrett Corporation	Rig II, LLC
1099 18th Street, Suite 2300	1582 West 2600 South
Denver, CO 80202	Woods Cross, UT 84087
CA Number(s):	Unit(s):

WELL INFORMATION:

Well Name	Sec	TWN	RNG	API	Entity	Mineral	Surface	Type	Status
See Attached List									

OPERATOR CHANGES DOCUMENTATION:

1. Sundry or legal documentation was received from the **FORMER** operator on:

10/21/2016

2. Sundry or legal documentation was received from the NEW operator on:

10/21/2016

3. New operator Division of Corporations Business Number:

8256968-0160

REVIEW:

1. Surface Agreement Sundry from NEW operator on Fee Surface wells received on:

N/A

2. Receipt of Acceptance of Drilling Procedures for APD on:

10/21/2016

3. Reports current for Production/Disposition & Sundries:

11/2/2016

4. OPS/SI/TA well(s) reviewed for full cost bonding:

11/3/2016

5. UIC5 on all disposal/injection/storage well(s) approved on:

11/3/2016

6. Surface Facility(s) included in operator change:

None

7. Inspections of PA state/fee well sites complete on (only upon operators request):

11/3/2016

NEW OPERATOR BOND VERIFICATION:

1. Federal well(s) covered by Bond Number:

UTB000712

2. Indian well(s) covered by Bond Number:

LPM 922467

3.State/fee well(s) covered by Bond Number(s):

9219529

DATA ENTRY:

1. Well(s) update in the OGIS on:

11/7/2016

2. Entity Number(s) updated in OGIS on:

11/7/2016

3. Unit(s) operator number update in OGIS on:

N/A

4. Surface Facilities update in OGIS on:

N/A

5. State/Fee well(s) attached to bond(s) in RBDMS on:

11/7/2016

6. Surface Facilities update in RBDMS on:

N/A

COMMENTS:

Well Name	Sec	TWN	RNG	API Number	Entity	Mineral	Surface	Туре	Status
SWD 9-36 BTR	9	030S	060W	4301350646	18077	Indian	Fee	WD	Α
16-6D-46 BTR SWD	6	040S	060W	4301350781	18327	Indian	Fee	WD	Α
6-32-36 BTR SWD	32	030S	060W	4301350921	18329	Indian	Fee	WD	Α
LC TRIBAL 8-26D-47	26	040S	070W	4301334024		Indian	Indian	OW	APD
16-21D-37 BTR	21	030S	070W	4301350758		Indian	Fee	OW	APD
14-11D-37 BTR	11	030S	070W	4301350862		Indian	Fee	OW	APD
7-17D-46 BTR	17	040S	060W	4301350883		Indian	Indian	OW	APD
14-12D-37 BTR	12	030S	070W	4301350894		Indian	Fee	ow	APD
1-18D-36 BTR	18	030S	060W	4301350922		Indian	Fee	OW	APD
13-2D-45 BTR	2	040S	050W	4301350931		Indian	Indian	OW	APD
5H-16-46 BTR	16	040S	060W	4301350992		Indian	Indian	OW	APD
9H-17-45 BTR	17	040S	050W	4301351098		Indian	Indian	OW	APD
13H-8-46 BTR UB	8	040S	060W	4301351124		Indian	Indian	OW	APD
8H-9-46 BTR	9	040S	060W	4301351140		Indian	Indian	ow	APD
LC TRIBAL 7-31D-37	31	030S	070W	4301351147		Indian	Fee	ow	APD
14-16D-45 BTR	16	040S	050W	4301351178	İ	Indian	Indian	ow	APD
16-19D-37 BTR	19	030S	070W	4301351179		Indian	Fee	OW	APD
6-2D-45 BTR	2	040S	050W	4301351234		Indian	Indian	ow	APD
2-2D-45 BTR	2	040S	050W	4301351235		Indian	Indian	OW	APD
10-26-35 BTR	26	030S	050W	4301351248		Indian	Fee	OW	APD
LC TRIBAL 1H-33-46	33	040S	060W	4301351257		Indian	Fee	OW	APD
LC TRIBAL 9-25D-46	25	040S	060W	4301351276		Indian	Indian	OW	APD
LC TRIBAL 8H-30-45	30	040S	050W	4301351277		Indian	Indian	OW	APD
LC TRIBAL 16H-30-45	30	040S	050W	4301351279		Indian	Indian	OW	APD
LC TRIBAL 13-30D-45	30	040S	050W	4301351282		Indian	Indian	OW	APD
LC TRIBAL 16H-36-46	36	040S	060W	4301351291		Indian	Indian	OW	APD
LC TRIBAL 13H-30-46	30	040S	060W	4301351321		Indian	Indian	OW	APD
LC TRIBAL 13H-31-46	31	040S	060W	4301351326		Indian	Indian	OW	APD
LC TRIBAL 16-31D-46	31	040S	060W	4301351328		Indian	Indian	OW	APD
LC TRIBAL 5H-26-47	26	040S	070W	4301351337		Indian	Indian	OW	APD
LC TRIBAL 5H-19-45	20	040S	050W	4301351349		Indian	Indian	OW	APD
LC TRIBAL 16-36D-47	36	040S	070W	4301351363		Indian	Indian	OW	APD
15-4D-47 BTR	4	040S	070W	4301351377		Indian	Fee	OW	APD
16-23D-46 LC TRIBAL	23	040S	060W	4301351396		Indian	Fee	OW	APD
15-2D-36 BTR	2	030S	060W	4301351419		Indian	Fee	OW	APD
16-23D-37 BTR	23	030S	070W	4301351420	1	Indian	Fee	ow	APD
11-9D-47 BTR	9	040S	070W	4301351422		Indian	Fee	OW	APD
15-13D-47 BTR	13	040S	070W	4301351424		Indian	Indian	OW	APD
LC TRIBAL 15-19D-46	19	040S	060W	4301351426	<u> </u>	Indian	Indian	ow	APD
16-13D-45 BTR	13	040\$	050W	4301351428		Indian	Indian	OW	APD

14-12D-45 BTR	12	040S	050W	4301351444	Indian	Indian	OW	APD
16-14D-45 BTR	14	040S	050W	4301351445	Indian	Indian	OW	APD
5-13D-45 BTR	13	040S	050W	4301351446	Indian	Indian	OW	APD
LC TRIBAL 16-26D-46	26	040S	060W	4301351450	Indian	State	OW	APD
LC TRIBAL 10-20D-40	34	0408	060W	4301351451				
16-12D-45 BTR	12	040S	050W	4301351451	Indian Indian	State Indian	OW	APD
8-12D-45 BTR	12	040S	050W	4301351452			OW	APD
LC TRIBAL 1-35D-46	35	040S	060W		Indian	Indian	OW	APD
16-25D-37 BTR		0405	070W	4301351454	Indian	Fee	OW	APD
LC TRIBAL 13H-29-46	25			4301351455	Indian	Fee	OW	APD
	28	0408	060W	4301351462	Indian	Fee	OW	APD
LC TRIBAL 14-30D-37	30	0308	070W	4301351494	Indian	Fee	OW	APD
7-13D-45 BTR	13	0408	050W	4301351497	Indian	Indian	OW	APD
LC TRIBAL 4H-35-46	35	0408	060W	4301351515	Indian	Fee	OW	APD
LC TRIBAL 13H-19-46	19	040\$	060W	4301351543	Indian	Indian	OW	APD
16-26D-37 BTR	26	030S	070W	4301351598	Indian	Fee	OW	APD
LC TRIBAL 16-31D-37	31	030\$	070W	4301351610	Indian	Fee	OW	APD
5-4-35 BTR	4	030S	050W	4301351613	Indian	Fee	OW	APD
LC TRIBAL 16-31D-47	31	040S	070W	4301351616	Indian	Indian	OW	APD
LC TRIBAL 13H-31-47	31	040S	070W	4301351617	Indian	Indian	OW	APD
LC TRIBAL 13-32D-47	32	040S	070W	4301351619	Indian	Indian	OW	APD
LC TRIBAL 16H-32-47	32	040S	070W	4301351620	Indian	Indian	OW	APD
LC TRIBAL 1-32D-47	32	040S	070W	4301351624	Indian	Indian	OW	APD
LC TRIBAL 4H-32-47	32	040S	070W	4301351625	Indian	Indian	OW	APD
LC TRIBAL 13-28D-47	28	040S	070W	4301351627	Indian	Indian	OW	APD
LC TRIBAL 13H-29-47	28	040S	070W	4301351628	Indian	Indian	OW	APD
LC TRIBAL 16H-28-47	28	040S	070W	4301351629	Indian	Indian	OW	APD
LC TRIBAL 1-28D-47	28	040S	070W	4301351639	Indian	Indian	OW	APD
LC TRIBAL 1H-27-47	28	040S	070W	4301351640	Indian	Indian	OW	APD
LC TRIBAL 4H-28-47	28	040S	070W	4301351641	Indian	Indian	OW	APD
LC TRIBAL 7-25D-58	25	050S	W080	4301351643	Indian	Indian	OW	APD
LC TRIBAL 6-25D-58	25	050S	080W	4301351644	Indian	Indian	OW	APD
LC TRIBAL 13H-24-58	24	050S	W080	4301351645	Indian	Indian	OW	APD
LC TRIBAL 16-24D-58	24	050S	080W	4301351646	Indian	Indian	OW	APD
LC Tribal 8-23D-46	23	040S	060W	4301351654	Indian	Fee	OW	APD
LC Tribal 16-35D-45	35	040S	050W	4301351656	Indian	Fee	OW	APD
LC Tribal 13H-35-45	35	040S	050W	4301351657	Indian	Fee	ow	APD
LC Tribal 16-36D-45	36	040S	050W	4301351658	Indian	Fee	ow	APD
LC Tribal 13H-36-45	36	040S	050W	4301351659	Indian	Fee	OW	APD
LC Tribal 5-36D-45	36	0408	050W	4301351661	Indian	Fee	OW	APD
LC Tribal 8-26D-46	26	040\$	060W	4301351663	Indian	Fee	OW	APD
3-29D-36 BTR	29	0308	060W	4301351665	Indian	Fee	OW	APD

LC Tribal 5-35D-45	35	040S	050W	4301351666	Indian	Fee	OW	APD
_C Tribal 5-24D-46	24	0408	060W	4301351668	Indian	Indian	ow	APD
_C TRIBAL 6-12D-58	12	0508	080W	4301351696	Indian	Indian	OW	APD
LC TRIBAL 8-12D-58	12	050S	080W	4301351697	Indian	Indian	OW	APD
.C TRIBAL 16H-22-47	21	040S	070W	4301351700	Indian	Indian	OW	APD
5-25D-37 BTR	25	030S	070W	4301351803	Indian	Fee	OW	APD
8-3D-36 BTR	3	0308	060W	4301351804	Indian	Fee	OW	APD
14-26D-37 BTR	26	0308	070W	4301351805	Indian	Fee	OW	APD
9-4-35 BTR	4	0308	050W	4301351806	Indian	Fee	ow	APD
11-4D-35 BTR	4	030S	050W	4301351807	Indian	Fee	OW	APD
16-27D-37 BTR	27	0308	070W	4301351808	Indian	Fee	OW	APD
14-27D-37 BTR	27	0308	070W	4301351809	Indian	Fee	OW	APD
14-16D-46 BTR	16	040S	060W	4301351812	Indian	Indian	OW	APD
_C Tribal 16-35D-48	35	040S	080W	4301351847	Indian	Indian	OW	APD
LC Tribal 13H-35-48	35	040S	080W	4301351848	Indian	Indian	OW	APD
_C Tribal 13-2D-58	11	050S	080W	4301351850	Indian	Indian	OW	APD
5-13D-36 BTR	13	0308	060W	4301351862	Indian	Fee	OW	APD
5-8D-36 BTR	8	0308	060W	4301351871	Indian	Fee	OW	APD
16-1D-36 BTR	1	0308	060W	4301351872	Indian	Fee	ow	APD
3-18D-46 BTR	18	040S	060W	4301351897	Indian	Fee	OW	APD
_C Tribal 5-36D-46	36	0408	060W	4301351905	Indian	Indian	OW	APD
LC Tribal 5-26D-45	26	040S	050W	4301351907	Indian	Indian	OW	APD
14-13D-45 BTR	13	040S	050W	4301351974	Indian	Indian	OW	APD
14-34D-46 DLB	34	040S	060W	4301351975	Indian	Fee	OW	APD
LC Tribal 5-21D-45	21	0408	050W	4301352001	Indian	Indian	OW	APD
_C Tribal 8-22D-45	22	0408	050W	4301352002	Indian	Indian	OW	APD
_C Tribal 8-25D-45	25	0408	050W	4301352007	Indian	Indian	OW	APD
LC Tribal 16-25D-45	25	040S	050W	4301352008	Indian	Indian	OW	APD
LC Tribal 16-22D-45	22	040S	050W	4301352009	Indian	Indian	OW	APD
LC Tribal 16-26D-45	26	040S	050W	4301352010	Indian	Indian	OW	APD
LC Tribal 14-31D-37	31	0308	070W	4301352016	Indian	Fee	OW	APD
5-12D-45 BTR	12	040S	050W	4301352030	Indian	Indian	ow	APD
LC Tribal 9-20D-45	20	040S	050W	4301352031	Indian	Indian	OW	APD
LC Tribal 13-35D-47	35	0408	070W	4301352055	Indian	Indian	ow	APD
C Tribal 1-23D-47	23	040S	070W	4301352057	Indian	Indian	ow =	APD
9-17D-46 BTR	17	040S	060W	4301352059	Indian	Indian	OW	APD
11-18D-46 BTR	18	040S	060W	4301352060	Indian	Indian	OW	APD
9-10D-47 BTR	10	040S	070W	4301352092	Indian	Fee	OW	APD
LC Tribal 1-17D-47	17	0408	070W	4301352096	Indian	Fee	OW	APD
7-35D-37 BTR	35	0308	070W	4301352115	Indian	Fee	OW	APD
14-25D-37 BTR	25	0308	070W	4301352116	Indian	Fee	OW	APD

LC Tribal 5-25-46	25	040S	060W	4301352126	Indian	Indian	OW	APD
8-33D-35 BTR	33	030S	050W	4301352161	Indian	Fee	OW	APD
5-4D-36 BTR	4	030S	060W	4301352175	Indian	Fee	OW	APD
'-4D-36 BTR	4	030S	060W	4301352176	Indian	Fee	OW	APD
C Tribal 4-36D-47	36	040S	070W	4301352186	Indian	Indian	OW	APD
.C Tribal 4-22D-46	22	040S	060W	4301352944	Indian	Indian	OW	APD
.C Tribal 16-22D-46	22	040S	060W	4301352945	Indian	Indian	OW	APD
.C Tribal 11-19D-46	19	040S	060W	4301352946	Indian	Indian	OW	APD
.C Tribal 7-20D-45	20	040S	050W	4301352947	Indian	Indian	OW	APD
5-11D-35 BTR	11	030S	050W	4301353056	Indian	Fee	OW	APD
3-11D-35 BTR	11	030S	050W	4301353057	Indian	Fee	OW	APD
3TR 16-36D-37	36	030S	070W	4301353059	Indian	Fee	OW	APD
I-29D-35 BTR	30	030S	050W	4301353060	Indian	Fee	ow	APD
-30D-35 BTR	30	030S	050W	4301353061	Fee	Fee	OW	APD
C TRIBAL 3-23D-46	23	040S	060W	4301353066	Indian	State	ow	APD
C Tribal 14-23D-46	23	040S	060W	4301353067	Indian	State	OW	APD
.C Tribal 13-25D-46	25	040S	060W	4301353068	Indian	Indian	OW	APD
C Tribal 14-26D-46	26	040S	060W	4301353069	Indian	State	OW	APD
C Tribal 5-26D-46	26	040S	060W	4301353070	Indian	State	OW	APD
C Tribal 11-35D-45	35	040S	050W	4301353071	Indian	State	OW	APD
C Tribal 7-35D-45	35	040S	050W	4301353072	Indian	State	OW	APD
C Tribal 3-35D-45	35	040S	050W	4301353075	Indian	State	OW	APD
C Tribal 14-36D-45	36	040S	050W	4301353076	Indian	State	OW	APD
C Tribal 13-36D-45	36	040S	050W	4301353077	Indian	State	OW	APD
C Tribal 10-36D-45	36	040S	050W	4301353078	Indian	State	OW	APD
.C Tribal 8-36D-45	36	040S	050W	4301353079	Indian	State	OW	APD
.C Tribal 6-36D-45	36	040S	050W	4301353080	Indian	State	OW	APD
.C Tribal 1-34D-46	34	040S	060W	4301353081	Indian	State	OW	APD
.C Tribal 9-27D-46	27	040S	060W	4301353082	Indian	State	OW	APD
.C Tribal 13-35D-45	35	040S	050W	4301353083	Indian	State	OW	APD
C Tribal 8-35D-45	35	040S	050W	4301353084	Indian	State	OW	APD
.C Tribal 15-35D-45	35	040S	050W	4301353085	Indian	State	OW	APD
C Tribal 12-25D-45	25	040S	050W	4301353122	Indian	Indian	OW	APD
C Tribal 14-25D-45	25	040S	050W	4301353123	Indian	Indian	OW	APD
C Tribal 10-25D-45	25	040S	050W	4301353124	Indian	Indian	ow	APD
C Tribal 11-26-45	26	040S	050W	4301353125	Indian	Indian	OW	APD
C Tribal 13-26D-45	26	040S	050W	4301353126	Indian	Indian	OW	APD
C Tribal 7-31D-46	31	040S	060W	4301353127	Indian	Indian	OW	APD
.C Tribal 7-19D-45	19	040S	050W	4301353128	Indian	Indian	OW	APD
.C Tribal 5-19D-45	19	040S	050W	4301353130	Indian	Indian	OW	APD
.C Tribal 7-25D-46	25	040S	060W	4301353132	Indian	Indian	OW	APD

	15.	1							
_C Tribal 7-24D-46	24	0408	060W	4301353134		Indian	Indian	OW	APD
.C Tribal 14-31D-46	31	040S	060W	4301353135		Indian	Indian	OW	APD
C Tribal 14-30D-46	30	040S	060W	4301353136		Indian	Indian	OW	APD
13-4-35 BTR SWD	4	030S	050W	4301353293		Fee	Fee	OW	APD
.C FEE 14-26D-47	26	040S	070W	4301353294	1	Fee	Indian	OW	APD
C Fee 5-25D-47	25	040S	070W	4301353295		Fee	Indian	OW	APD
7-35-46 LC SWD	35	040S	060W	4301353296		Fee	Fee	OW	APD
.C Fee 1H-33-47	32	040S	070 W	4301353309		Fee	Indian	ow	APD
_C FEE 14-2D-58	2	050S	W080	4301353312		Fee	Indian	OW	APD
C FEE 13H-21-47	21	040S	070W	4301353313		Fee	Indian	OW	APD
C Fee 16-21D-47	21	040S	070W	4301353326		Fee	Indian	OW	APD
6-7D-46 BTR	7	040S	060W	4301353328		Fee	Indian	OW	APD
C Fee 15-26D-47	26	040S	070W	4301353331		Fee	Indian	OW	APD
.C Fee 4-24D-47	23	040S	070W	4301353332		Fee	Indian	OW	APD
.C Fee 5-34D-47	34	040S	070W	4301353333		Fee	Indian	OW	APD
.C Fee 5-35D-47	35	040S	070W	4301353334	:	Fee	Indian	OW	APD
3-34D-47 LC Fee	34	040S	070W	4301353337		Fee	Indian	OW	APD
4-35D-35 BTR	35	030S	050W	4301352120		Fee	Fee	ow	DRL
-17D-46 BTR	17	040S	060W	4301351078		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301351187		Indian	Fee	OW	OPS
5-10D-45 BTR	10	040S	050W	4301351221		Indian	Indian	OW	OPS
-3D-45 BTR	3	040S	050W	4301351810		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301352117		Fee	Fee	OW	OPS
-35D-35 BTR	35	030S	050W	4301352118		Fee	Fee	OW	OPS
-2D-46 BTR	2	040S	060W	4301353086		Indian	Fee	OW	OPS
'-21-46 DLB	21	040S	060W	4301333567	16526	Indian	Indian	OW	P
.C TRIBAL 1H-27-46	27	040S	060W	4301333568	18175	Indian	Fee	GW	P
'-29-46 DLB	29	040S	060W	4301333584	17603	Indian	Fee	GW	P
C TRIBAL 12H-28-46	28	0408	060W	4301333631	18132	Indian	Indian	GW	P
C TRIBAL 13H-21-46	21	0408	060W	4301333632	18107	Indian	Indian	GW	 P
2-36-36 BTR	36	030S	060W	4301333638	16336	Indian	Fee	GW	P
i-5-46 BTR	5	0408	060W	4301333639	16542	Indian	Fee	OW	P
5-23-36 BTR	23	0308	060W	4301333642	16675	Indian	Fee	GW	P
4-29-36 BTR	29	030S	060W	4301333643	16725	Indian	Fee	ow	P
4-30-36 BTR	30	0308	060W	4301333644	16701	Indian	Fee	GW	<u>'</u>
'-20-46 DLB	20	040S	060W	4301333657	16584	Indian	Indian	OW	'P
.C TRIBAL 5-21D-46	21	0408	060W	4301333658	18887	Indian	Indian	OW	P
-20-46 DLB	20	0408	060W	4301333659	18750	Indian	Indian	GW	P
.C TRIBAL 13H-20-46	20	0408	060W	4301333678	17979	Indian	Indian	GW	P
14-7-46 BTR	7	0408	060W	4301333806	16890	Indian	Indian	GW	P
	1.	0.00	100011	TOO OOOOOO	10000	HIMIAII	HIMIAH	UVV	1 1-1

1-5-45 BTR	5	040S	050W	4301333868	16931	Indian	Indian	OW	Р
5-16-36 BTR	16	030S	060W	4301333970	17195	Indian	Fee	ow	P
5-29-36 BTR	29	030S	060W	4301333972	17557	Indian	Fee	ow	P
4-30-36 BTR	30	030S	060W	4301333973	17249	Indian	Fee	ow	P
7-19-46 DLB	19	040S	060W	4301334004	19018	Indian	Indian	OW	Р
5-25-36 BTR	25	030S	060W	4301334021	17126	Fee	Fee	OW	Р
5-4-45 BTR	4	0408	050W	4301334089	17507	Indian	Indian	oW	Р
13-2-46 BTR	2	040S	060W	4301334090	18618	Indian	Indian	ow	Р
2-3-45 BTR	3	040S	050W	4301334099	17932	Indian	Indian	OW	Р
7-6-45 BTR	6	040S	050W	4301334100	17653	Indian	Indian	OW	Р
1-9-45 BTR	9	040S	050W	4301334101	17910	Indian	Indian	OW	P
8-10-45 BTR	10	040S	050W	4301334102	17530	Indian	Indian	ow	Р
7-17-45 BTR	17	040S	050W	4301334104	17933	Indian	Indian	OW	Р
16-7-45 BTR	7	040S	050W	4301334111	17665	Indian	Indian	OW	Р
15-18-45 BTR	18	040S	050W	4301334112	17832	Indian	Indian	ow	P
6-12-46 BTR	12	040S	060W	4301334114	17964	Indian	Indian	ow	P
5-13-46 BTR	13	040S	060W	4301334115	17833	Indian	Indian	OW	Р
16-26-36 BTR	26	030S	060W	4301334132	18028	Indian	Fee	OW	P
1-23-36 BTR	23	030S	060W	4301334136	17722	Indian	Fee	OW	Р
15-10-36 BTR	10	030S	060W	4301334277	17419	Indian	Fee	OW	Р
14-5-46 BTR	5	040S	060W	4301350307	17624	Fee	Fee	OW	Р
14X-22-46 DLB	22	040S	060W	4301350351	17604	Indian	Indian	ow	Р
16-13-36 BTR	13	030S	060W	4301350372	17853	Indian	Fee	ow	Р
5-33-46 DLB	33	040S	060W	4301350397	17765	Indian	Fee	OW	Р
5-34-46 DLB	34	040S	060W	4301350415	17801	Indian	State	GW	Р
LC FEE 12H-32-46	32	040S	060W	4301350431	18003	Fee	Fee	OW	Р
1-13D-47 BTR	13	040S	070W	4301350445	18205	Indian	Fee	OW	Р
16-8D-45 BTR	8	040S	050W	4301350466	18799	Indian	Indian	OW	Р
7-13D-46 BTR	13	040S	060W	4301350470	18076	Indian	Indian	OW	Р
14-8D-45 BTR	8	040S	050W	4301350567	18207	Indian	Indian	OW	Р
14-5D-45 BTR	5	040S	050W	4301350568	18108	Indian	Indian	OW	Р
16-31D-36 BTR	31	030S	060W	4301350573	18004	Indian	Fee	OW	P
5-7D-46 BTR	7	040S	060W	4301350574	18176	Indian	Indian	OW	Р
LC TRIBAL 13H-33-46	34	040S	060W	4301350575	18223	Indian	State	OW	Р
5-8-45 BTR	8	040S	050W	4301350607	18279	Indian	Indian	OW	Р
16-6D-45 BTR	6	040S	050W	4301350610	18177	Indian	Indian	OW	P
5-18D-45 BTR	18	040S	050W	4301350611	18300	Indian	Indian	OW	Р
7-26-37 BTR	26	030\$	070W	4301350641	18131	Indian	Fee	OW	Р
3-11D-36 BTR	11	030S	060W	4301350642	18299	Indian	Fee	OW	P
16-1D-46 BTR	1	040S	060W	4301350675	18525	Indian	Indian	ow	Р
14-3-45 BTR	3	040S	050W	4301350676	18363	Indian	Indian	ow	Р

4-17D-45 BTR	17	040S	050W	4301350687	18517	Indian	Indian	OW	Р
5-6D-45 BTR	6	040S	050W	4301350688	18726	Indian	Indian	OW	Р
7-7D-45 BTR	7	040S	050W	4301350689	18380	Indian	Indian	OW	P
14-10D-45 BTR	10	040S	050W	4301350754	18447	Indian	Indian	OW	P
14-9D-45 BTR	9	040S	050W	4301350755	18379	Indian	Indian	OW	P
13-16D-36 BTR	16	030S	060W	4301350757	18206	Indian	State	OW	Р
5-9D-36 BTR	9	030S	060W	4301350843	18381	Indian	Fee	ow	P
16-5D-46 BTR	5	040S	060W	4301350844	18280	Fee	Fee	OW	Р
5-27D-37 BTR	27	030S	070W	4301350847	18526	Indian	Fee	OW	Р
7-4D-45 BTR	4	040S	050W	4301350884	18562	Indian	Indian	OW	Р
2-16D-45 BTR	16	040S	050W	4301350899	18619	Indian	Indian	OW	P
16-10D-45 BTR	10	040S	050W	4301350902	18725	Indian	Indian	OW	P
5-2D-36 BTR	2	030S	060W	4301350913	18886	Indian	Fee	OW	Р
13H-27-36 BTR	27	030S	060W	4301350918	18445	Indian	State	OW	P
8-16D-46 BTR	16	040S	060W	4301350953	19027	Indian	Indian	OW	Р
16-16D-46 BTR	16	040S	060W	4301350956	19028	Indian	Indian	OW	P
16-9D-45 BTR	9	040S	050W	4301350962	18662	Indian	Indian	OW	Р
14-31D-36 BTR	31	030S	060W	4301350973	18524	Indian	Fee	OW	Р
5-10D-36 BTR	10	030S	060W	4301350978	18989	Indian	Fee	OW	Р
1-32D-36 BTR	32	030S	060W	4301350979	18648	Indian	Fee	OW	Р
16-12D-36 BTR	12	030S	060W	4301350980	18748	Indian	Fee	ow	Р
2-18D-45 BTR	18	040S	050W	4301350991	18776	Indian	Indian	OW	P
3-1-46 BTR	1	040S	060W	4301351017	18777	Indian	Fee	ow	Р
10-5-45 BTR	5	040S	050W	4301351062	18724	Indian	Indian	OW	Р
12-4D-45 BTR	4	040S	050W	4301351063	18813	Indian	Indian	ow	Р
1-10D-45 BTR	10	040S	050W	4301351064	18966	Indian	Indian	ow	Р
16-2D-46 BTR	2	040S	060W	4301351079	18830	Indian	Indian	OW	Р
9H-4-45 BTR	4	040S	050W	4301351092	18814	Indian	Indian	OW	Р
12-17-45 BTR	17	040S	050W	4301351097	18984	Indian	Indian	OW	Р
5-9D-46 BTR	9	040S	060W	4301351109	19313	Indian	Fee	OW	Р
14-9D-36 BTR	9	030S	060W	4301351144	19004	Indian	Fee	OW	Р
5-31D-36 BTR	31	030S	060W	4301351146	18691	Indian	Fee	ow	Р
4-9D-45 BTR	9	040S	050W	4301351157	18883	Indian	Indian	OW	Р
8-12D-46 BTR	12	040S	060W	4301351159	18911	Indian	Indian	OW	Р
LC TRIBAL 16-23D-47	23	040S	070W	4301351180	18617	Indian	Indian	OW	Р
14-7D-45 BTR	7	040S	050W	4301351222	18949	Indian	Indian	OW	Р
5-16D-45 BTR	16	040S	050W	4301351223	18987	Indian	Indian	OW	P
4-5D-45 BTR	5	040S	050W	4301351242	18882	Indian	Indian	OW	P
LC TRIBAL 16H-19-45	19	040S	050W	4301351278	18627	Indian	Indian	OW	Р
LC TRIBAL 13-19D-45	19	040S	050W	4301351280	18628	Indian	Indian	OW	Р
LC TRIBAL 5-30D-45	30	040S	050W	4301351281	19448	Indian	Indian	ow	Р

LC TRIBAL 15-24D-46	24	040S	060W	4301351283	18626	Indian	Indian	OW	Р
LC TRIBAL 13H-24-46	19	040S	050W	4301351289	18629	Indian	Indian	ow	P
7-16-47 BTR	16	040S	070W	4301351296	18950	Indian	Fee	ow	P
14-18D-45 BTR	18	040S	050W	4301351313	19005	Indian	Indian	ow	Р
LC TRIBAL 16-30D-46	30	040S	060W	4301351320	19006	Indian	Indian	OW	Р
LC TRIBAL 5-20D-45	20	040S	050W	4301351331	19449	Indian	Indian	OW	Р
11-8D-46 BTR	8	040\$	060W	4301351336	19314	Indian	Indian	OW	Р
5-7D-45 BTR	7	040S	050W	4301351350	18951	Indian	Indian	OW	Р
7-5-35 BTR	5	0308	050W	4301351599	19078	Indian	Fee	OW	Р
13-5D-35 BTR	5	030S	050W	4301351600	18996	Indian	Fee	OW	Р
11-5D-35 BTR	5	030S	050W	4301351601	19061	Fee	Fee	OW	Р
15-5D-35 BTR	5	030S	050W	4301351602	19062	Fee	Fee	OW	Р
9-5D-35 BTR	5	030S	050W	4301351609	19029	Indian	Fee	OW	Р
3-5D-35 BTR	5	030S	050W	4301351638	19079	Indian	Fee	OW	Р
7-8-46 BTR	8	040S	060W	4301351702	19315	Indian	Indian	OW	P
7-30-46 DLB	30	040S	060W	4301351703	18997	Fee	Indian	OW	Р
3-13D-46 BTR	13	040S	060W	4301351718	18881	Indian	Indian	OW	Р
2-13D-46 BTR	13	040S	060W	4301351719	18885	Indian	Indian	OW	Р
12-12D-46 BTR	12	040S	060W	4301351720	18867	Indian	Indian	OW	∱P
10-12D-46 BTR	12	040S	060W	4301351721	18856	Indian	Indian	OW	P
11-11D-47 BTR	11	040S	070W	4301352091	19633	Fee	Fee	OW	Р
7-12D-47 BTR	12	040S	070W	4301352094	19600	Indian	Fee	ow	Р
5-12D-47 BTR	12	040S	070W	4301352095	19634	Indian	Fee	ow	Р
14-33D-35 BTR	33	030S	050W	4301352162	19450	Indian	Fee	OW	Р
16-33D-35 BTR	33	030S	050W	4301352163	19451	Indian	Fee	OW	Р
14-22-46 DLB	22	040S	060W	4301333660	17604	Indian	Indian	D	PA
13H-31-36 BTR	31	0308	060W	4301350465	18485	Indian	Fee	OW	PA
16X-23D-36 BTR	23	030S	060W	4301350623	18007	Indian	State	OW	PA
8-6-45 BTR	6	040S	050W	4301350900	18561	Indian	Indian	OW	PA
13-13-36 BTR	13	030S	060W	4301350919	18364	Indian	Fee	OW	PA
7-28-46 DLB	28	040S	060W	4301333569	16460	Indian	Indian	OW	S
5-21-36 BTR	21	030S	060W	4301333641	16674	Indian	Fee	GW	S
13-26-36 BTR	26	030S	060W	4301333980	17569	Indian	Fee	OW	S
14-1-46 BTR	1	040S	060W	4301334113	18516	Indian	Indian	OW	S
16-21-36 BTR	21	030S	060W	4301334130	17721	Indian	Fee	OW	S
14-21-36 BTR	21	030S	060W	4301334131	18006	Indian	Fee	OW	S
7-16-36 BTR	16	030\$	060W	4301334133	17834	Indian	Fee	OW	S
1-30-36 BTR	30	0308	060W	4301334134	17905	Indian	Fee	ow	S
16-30-36 BTR	30	0308	060W	4301334135	18005	Indian	Fee	OW	S
3-23-36 BTR	23	030\$	060W	4301334137	17860	Indian	Fee	OW	S
16-16-36 BTR	16	030S	060W	4301334138	17666	Indian	Fee	OW	S

4-26-36 BTR	26	030S	060W	4301334139	17620	Fee	Fee	OW	S
9-11-36 BTR	11	030S	060W	4301334276	17451	Indian	Fee	OW	S
3-36-36 BTR	36	030S	060W	4301350398	17955	Indian	Fee	OW	S
7-10-36 BTR	10	030S	060W	4301350437	18052	Indian	Fee	OW	S
16-12D-46 BTR	12	040S	060W	4301350467	18051	Indian	Indian	OW	S
13H-13-46 BTR	13	040S	060W	4301350468	18208	Indian	Indian	OW	S
13-12-46 BTR	12	040S	060W	4301350469	18233	Indian	Indian	OW	S
14-8D-36 BTR	8	030S	060W	4301350612	18163	Indian	Fee	OW	S
14-7D-36 BTR	7	030S	060W	4301350613	18330	Indian	Fee	ow	S
16-9-36 BTR	9	0308	060W	4301350645	18078	Indian	Fee	OW	S
7-27-37 BTR	27	030S	070W	4301350647	18090	Indian	Fee	OW	S
16-12D-37 BTR	12	030S	070W	4301350785	18446	Indian	Fee	OW	S
14-21D-37 BTR	21	030S	070W	4301350859	18548	Indian	Fee	OW	S
10-18D-36 BTR	18	030S	060W	4301350915	18884	Indian	Fee	OW	S
5-27D - 36	27	030S	060W	4301350917	18482	Indian	State	ow	S
10-36D-36 BTR	36	030S	060W	4301351005	18523	Indian	Fee	OW	S
14-6D-45 BTR	6	040S	050W	4301351158	18967	Indian	Indian	ow	S
5H-1-46 BTR UTELAND BUTTE	6	040S	050W	4301351215	18728	Indian	Indian	OW	S
5H-1-46 BTR WASATCH	6	040S	050W	4301351216	18727	Indian	Indian	OW	S
1-25D-36 BTR	25	030S	060W	4301351294	18798	Indian	Fee	OW	S
5-5D-35 BTR	5	030S	050W	4301351605	19055	Indian	Fee	OW	S
16-23-36 BTR	23	030S	060W	4301333971	17182	Indian	Fee	OW	TA
LC TRIBAL 14-23D-47	23	040S	070W	4301334022	18616	Indian	Indian	OW	TA
5-32D-36 BTR	32	030S	060W	4301350756	18328	Indian	Fee	OW	TA



October 20, 2016

RECEIVED

OCT 21 2016

Re: Bill Barrett Corporation Transfer to New Operator

DIV. OF OIL, GAS & MINING

Dear Ms. Medina:

Attached please find the change of operation Form 9, Form 5's and Request to Transfer APD formchanging the operator from Bill Barrett Corporation to RIG II, LLC, effective 11/1/2016. Badlands Energy – Utah, LLC will be a sub-operator.

New Operator Contact information:

RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 Telephone:(801) 683-4245 Fax:(801) 298-9889

Upon reviewing the attached, please contact myself with any questions at 303-312-8115.

Sincerely,

Bill Barrett Corporation

Brady Riley Permit Analyst

STATE OF UTAH FORM 9 **DEPARTMENT OF NATURAL RESOURCES** 5. LEASE DESIGNATION AND SERIAL NUMBER: DIVISION OF OIL, GAS AND MINING (see attached well list) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME: SUNDRY NOTICES AND REPORTS ON WELLS N/A 7, UNIT or CA AGREEMENT NAME: Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. 1. TYPE OF WELL 8. WELL NAME and NUMBER OIL WELL 🔽 GAS WELL (see attached well list) 2. NAME OF OPERATOR: 9. API NUMBER RIG II, LLC 3. ADDRESS OF OPERATOR PHONE NUMBER: 10. FIELD AND POOL, OR WILDCAT: 1582 West 2600 South (801) 683-4245 STATE UT ZIP 84087 Wood Cross 4. LOCATION OF WELL FOOTAGES AT SURFACE: (see attached well list) COUNTY: QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: STATE: UTAH CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 11. TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE REPERFORATE CURRENT FORMATION NOTICE OF INTENT (Submit in Duplicate) ALTER CASING FRACTURE TREAT SIDETRACK TO REPAIR WELL Approximate date work will start; CASING REPAIR **NEW CONSTRUCTION** TEMPORARILY ABANDON 11/1/2016 CHANGE TO PREVIOUS PLANS OPERATOR CHANGE TUBING REPAIR CHANGE TUBING PLUG AND ABANDON VENT OR FLARE SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK WATER DISPOSÁL (Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME) WATER SHUT-OFF Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE OTHER: CONVERT WELL TYPE **RECOMPLETE - DIFFERENT FORMATION** 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. RIG II, LLC IS SUBMITTING THIS SUNDRY AS NOTIFICATION THAT THE WELLS LISTED ON THE ATTACHED LIST HAVE BEEN SOLD TO-Rig II, LLC BY BILL BILL BARRETT CORPORATION EFFECTIVE 11/1/2016. PLEASE REFER ALL FUTURE CORRESPONDENCE TO THE ADDRESS BELOW. RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 801-683-4245 (STATE/FEE BOND # 9219529/ BLM BOND # UTB000712/ BIA BOND # LPM9224670) BILL BARRETT CORPORATION NOILS RIG II, LLC MAME (PLEASE PRINT) _ NAME (PLEASE PRINT) SIGNATURE SIGNATURE EH&S, Government and Regulatory Affairs Jesse McSwain Manager NAME (PLEASE PRINT) 1012016

APPROVED

NOV 0 7 2016

(This space for State use only)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

Request to Transfer Application or Permit to Drill

Well name:		(See attached lis	st)			
API number:						
Location:		Qtr-Qtr:	Section:	Township: Range:		
Company that	filed original application:	Bill Barrett Corpo	oration			
Date original pe	ermit was issued:					
Company that	permit was issued to:	Bill Barrett Cor	poration			
			÷			
Check one		Desi	red Action:			
Transfor	pending (unapproved) App	lication for Po	rmit to Drill to no	w operator		
submitted	in the pending Application fo	or Permit to Dril	l, remains valid ar	by verifies that the information as nd does not require revision. The cedures as stated in the application	new	
✓ Transfer	approved Application for P	ermit to Drill t	o new operator			
				ermitted, hereby verifies that the remains valid and does not requir	e	
		-41441			Τ.,	Ι
	checklist of some items rela		Tilication, which s	snould be verified.	Yes	No
· · · · · · · · · · · · · · · · · · ·	vate land, has the ownership				√	
	the surface agreement been				1	✓
Have any wells requirements for	been drilled in the vicinity of t r this location?	he proposed w	ell which would af	fect the spacing or siting		✓
Have there beer proposed well?	າ any unit or other agreement	ts put in place t	hat could affect th	e permitting or operation of this		✓
Have there been proposed location		route including	ownership or righ	t-of-way, which could affect the		✓
Has the approve	ed source of water for drilling	changed?				✓
	n any physical changes to the was discussed at the onsite		on or access route	which will require a change in		1
ls handing still in	n place, which covers this pro	posed well? B	ond No. 9219529-UDOGM/U	JTB000712-BI,M / LPM9224670-BIA	1	
13 Donaing Still II					_	rad
Any desired or r should be filed on necessary supp	on a Sundry Notice, Form 9, c orting information as required	or amended Ap	olication for Permi	n for Permit to Drill that is being tr it to Drill, Form 3, as appropriate,		rea,
Any desired or r should be filed of necessary support	on a Sundry Notice, Form 9, c	or amended Ap	Title Manager			rea,
Any desired or r should be filed of necessary support Name (please p Signature	on a Sundry Notice, Form 9, c orting information as required	or amended Ap	olication for Permi			

The person signing this form must have legal authority to represent the company or individual(s) to be listed as the new operator on the Application for Permit to Drill.

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL, GAS AND MINING

•	TRAI	NSFE	R OF	AUTHORITY TO INJECT	•
Well Name and Number 6-32-36 BTR SWD		4			API Number 4301350921
Location of Well				DUQUENOE	Field or Unit Name CEDAR RIM
Footage: 1628 FNL 1553 FWL QQ, Section, Township, Range: SENW	32	3S	6W	County : DUCHENSE State : UTAH	Lease Designation and Number 2OG0005608

EFFECTIVE DATE OF TRANSFER: 11/1/2016

CURRENT OP	PERATOR	
Company:	BILL BARRETT CORPORATION	Name: Duane Zavadil
Address:	1099 18th Street Ste 2300	Signature: 2nCd
	city DENVER state CO zip 80202	Senior Vice President - Title: EH&S, Government and Regulatory Affairs
Phone:	(303) 293-9100	Date: 10 20 16
Comments	· · · · · · · · · · · · · · · · · · ·	

Address: 1582 West 2600 South Signature: Signature: Manager	Company: RIG II, LLC Name: Jesse McSwain	
10/2 . 111	1593 West 2000 Courts	R:
(004) 002 4045	city Wood Cross state UT zip 84087 Title: Manager	
Phone: (801) 683-4245 Date: 10 LO 10	Phone: (801) 683-4245 Date: 10 20 10	

(This space for State use only)

Transfer approved by:

Approval Date: ///3//L

Comments:

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	JTHORITY TO INJECT	Γ
Well Name and 16-6D-46 BT			API Number 4301350781
ocation of Well		:	Field or Unit Name
Footage: 02	200 FSL 0099 FEL	County : DUCHESNE	ALTAMONT Lease Designation and Number
QQ, Section,	Township, Range: SESE 6 4S 6W	State: UTAH	20G0005608
	11/1/2016		
EFFECTIVE L	DATE OF TRANSFER: 11/1/2016		
CURRENT OP	PERATOR		
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil
Address:	1099 18th Street Ste 2300	Signature:	m Zinal
	city DENVER state CO zip 80202	SeniorV	ice President - Government and Regulatory Affairs
Phone:	(303) 293-9100	Date:	20/16
Comments:			
oommonto.	•		
NEW OPERAT			
VEW OF LINA	iok		
Company:	RIG II, LLC	Name: Jesse	McSwain ⁽
Address:	1582 West 2600 South	Signature:	Leve MG:
, , , , , , , , , , , , , , , , , , , ,	city Wood Cross state UT zip 84087	Title: Mana	
Phone:	(801) 683-4245	Date:	120/16
Comments:	:		
This space for S	state use only)	· ·	1
Transfer ap	oproved by:	Approval Date:	11/3/16
	Title: VIC		•

Comments:

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	UTHORITY TO INJECT	Γ
Vell Name and N SWD 9-36 B			API Number 4301350646
ocation of Well			Field or Unit Name CEDAR RIM
Footage: 05	539 FSL 0704 FEL	County : DUCHESNE	Lease Designation and Number
QQ, Section,	Township, Range: SESE 9 3S 6W	State: UTAH	2OG0005608
FFECTIVE D	PATE OF TRANSFER: 11/1/2016		
URRENT OP	ERATOR		
	DUL DADDETT CODDODATION	_	
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil
Address:	1099 18th Street Ste 2300	Signature: Senior V	ice kiesident -
	city DENVER state CO zip 80202	Title: EH&S, C	Government and Regulatory Affairs
Phone:	(303) 293-9100	Date: <u>\</u>	2014
Comments:			
EW OPERAT	OR		
Company:	RIG II, LLC	Name: Jesse	McSwain
Address:	1582 West 2600 South	Signature:	ene MG:
	city Wood Cross state UT zip 84087	Title: Mana	ger
Phone:	(801) 683-4245	Date:	20/14
Comments:			
sis annag far Ct	ofe use only)		
nis space for St			
Transfer ap	proved by:		
	Title:	-/A. IICE	PA.
Comm	nents: This well was approved with	rived 49 USC	, , , ,
	FPA approved Wi	Il be required	
	<u> </u>	V	